

New Product Information



- All line up has adopted single cylinder type (monotube), full length adjustable shock absorber.
Single cylinder/upright structure is adapted to all lineups. By 46mm of wide and low friction piston (Excluded to some vehicle), controlling initial attenuation delay, realizing smooth and flexible ride ability.
- Adopted Sub tank structure.
Adopted sub tank structure, maintain oil level and enough damping force from very low speed. Abolished hose line peculiar structure of sub tank (Excluded to some vehicle), reducing trouble when installing.
- 32 way of damping force adjustment
Adopted 2 WAY damping force adjustment of expansion 32 / contraction 32. Wide range adjustment balancing makes high dimension of controllability and comfortable driving feeling, from street to Circuit.
- High endurance of shock absorber.
Using high quality materials, Black chrome plated adapted to cylinder case and Nickel plated and special coating (Alumite coating for Aluminum) adapted to improving of corrosion-resistance.

Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code
NISSAN							
SILVIA	99/01-	S15	SR20DE,SR20DET	¥270,900	¥258,000	93123	4959094931232

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice

Product Information							
Vehicle	Model	Set Spring		Adjustable Range		Remarks	Code No.
		Front	Rear	Front	Rear		
NISSAN							
SILVIA	S15	100k 180mm Straight SP	8.0k 220mm Straight SP	-54~16	-72~0	100mm Damping Rate Extension Cable Included	93123

Adjustable Range may have the different depends on the vehicle.

Set Spring ... kgf/mm

※Please see our website http://www.blitz.co.jp/products/suspension/damper_zz-r_spec-c.htm for more details.