BL/TZ <u>information</u>

No. 2012-0023EN 2012/3/28 Blitz Co., Ltd.

New Product information



- Mono tube type shock absorber is used for all lineup:
 Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.
- Damping rates are 32-way adjustable for both front and rear:

Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.

High Durability is achieved:

Red anodized, forged aluminum upper mounts, matt black painted brackets, and black chrome plated cylinder cases are used for anti-corrosion performance. To extend the life of the pillow ball, bearings type upper seats are used for strut type applications..

Can be overhauled:

DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information										
Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code			
LEXUS										
HS250h	09/07-	ANF10	2AZ-FXE	¥165,900	¥158,000	92444	4959094924449			
TOYOTA										
SAI	09/12-	AZK10	2AZ-FXE	¥165,900	¥158,000	92444	4959094924449			
NISSAN										
CUBE	02/10-08/11	BZ11,YZ11	CR14DE,HR15DE	V4.0E.000	¥158,000	92456	4959094924562			
CUBE CUBIC	03/09-08/11	BGZ11,YGZ11	CR14DE,HR15DE	¥165,900						
SUBARU										
IMPREZA	92/11-00/08	GC8	EJ20 Turbo	¥176,400	¥168,000	92454	4959094924548			

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice

·	3	·	Product	Information	<u> </u>		
Vehicle		Set Spring		Adjustable Range			
	Model	Front	Rear	Front	Rear	Remarks	Code No.
LEXUS,TOYOTA	\						
HS250h	ANF10	6.0k	7.0k 180mm BS	-60 ~ +20	-50 ~ -15		
SAI	AZK10	180mm ST					92444
NISSAN							
CUBE	BZ11,YZ11	4.0k	5.0k 150mm BS	−75 ~ +10	-55 ~ -25		
CUBE CUBIC	BGZ11,YGZ11	220mm ST		-80 ~ 0	-60 ~ -30		92456
SUBARU							
IMPREZA	GC8	7.0k 200mm ST	5.0k 220mm ST	−55 ~ +20	-50 ~ +20	w/Damping Rate Extension Cable 150mm	92454

[%]To install damping Rate Extension cable needs making holes to panel or speaker board.

Adjustable Range may have the different depends on the vehicle.

Set Spring · · · kgf/mm

XPlease see our website http://www.blitz.co.jp/products/suspension/damper_zz-r.html for more details.

Now On Sale

^{**}Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.