## BL/TZ INFORMATION

No. 2012-0024EN 2012/3/28 Blitz Co., Ltd.

## **New Product Information**



All line up has adopted single cylinder type (monotube), full length adjustable shock absorber.

Single cylinder/upright structure is adapted to all lineups. By 46mm of wide and low friction piston (Excluded to some vehicle), controlling initial attenuation delay, realizing smooth and flexible ride ability.

Adopted Sub tank structure.

Adopted sub tank structure, maintain oil level and enough damping force from very low speed. Abolished hose line peculiar structure of sub tank (Excluded to some vehicle), reducing trouble when installing.

●32 way of damping force adjustment

Adopted 2 WAY damping force adjustment of expansion 32 / contraction 32. Wide range adjustment balancing makes high dimension of controllability and comfortable driving feeling, from street to Circuit.

• High endurance of shock absorber.

Using high quality materials, Black chrome plated adapted to cylinder case and Nickel plated and special coating (Alumite coating for Aluminum) adapted to improving of corrosion-resistance.

Product Information							
Vehicle	Model	Set Spring		Adjustable Range			
		Front	Rear	Front	Rear	Remarks	Code No.
TOYOTA							
COROLLA LEVIN	-AE86	8.0k 180mm	6.0k 160mm BS	<b>-52∼0</b>	-69 <b>~</b> -8	Spindle 付	93121
SPRINTER TRUENO		ST					

\*\*Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.

Adjustable Range may have the different depends on the vehicle.

Set Spring  $\cdots$  kgf/mm

XPlease see our website <a href="http://www.blitz.co.jp/products/suspension/damper\_zz-r\_spec-c.htm">http://www.blitz.co.jp/products/suspension/damper\_zz-r\_spec-c.htm</a> for more details.

Now On Sale