BLFTZ INFORMATION

No. 2012-0032EN 2012/3/28 BLITZ Co., Ltd.

Additional Application



• Mono tube type shock absorber is used for all lineup:

Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.

• Damping rates are 32-way adjustable for both front and rear:

Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
High Durability is achieved:

Red anodized, forged aluminum upper mounts, matt black painted brackets, and black chrome plated cylinder cases are used for anti-corrosion performance. To extend the life of the pillow ball, bearings type upper seats are used for strut type applications..

• Can be overhauled:

DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information										
Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code			
ΤΟΥΟΤΑ	1					I				
AQUA	11/12-	NHP10	1NZ-FXE	¥165,900	¥158,000	92798	4959094927983			

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice

Product Information											
Vehicle	Model	Set Spring		Adjustable Range							
		Front	Rear	Front	Rear	Remarks	Code No.				
ΤΟΥΟΤΑ	I										
AQUA	NHP10	5.0k 200mm ST	3.0k 190mm BS	-90~-30	-65~-20	延長ダイヤル付属なし	92798				

Adjustable Range may have the different depends on the vehicle.

Set Spring •••• kgf/mm

Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.

%Please see our website <u>http://www.blitz.co.jp/products/suspension/damper_zz-r.html</u> for more details.

http://www.blitz.co.jp/