BL#TZ INFORMATION

No. 2012-0074EN 2012/7/5 Blitz Co., Ltd.

Additional Application



• Mono tube type shock absorber is used for all lineup:

Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.

• Damping rates are 32-way adjustable for both front and rear:

Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
High Durability is achieved:

Red anodized, forged aluminum upper mounts, matt black painted brackets, and black chrome plated cylinder cases are used for anti-corrosion performance. To extend the life of the pillow ball, bearings type upper seats are used for strut type applications..

• Can be overhauled:

DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information												
Vehicle	Model Year Model		E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code					
NISSAN		I				ļ						
SKYLINE	01/06-06/11	V35,HV35,PV35	VQ25DD,VQ30DD,VQ35DE	¥165.900	¥158,000	92761	4959094927617					
(G35)	03/01-06/11	CPV35	VQ35DE	¥105,900								

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice

Product Information												
		Spring		Adjustable Range								
Vehicle	Model	Front	Rear	Front	Rear	Remarks	Code No.					
NISSAN												
SKYLINE (G35)	V35,HV35 PV35,CPV35	10.0k 200mm ST	8.0k 230mm BS	-75~0	-59~-17		92761					

Adjustable Range may have the different depends on the vehicle.

Set Spring •••• kgf/mm

 $\ensuremath{\mathbbmm{X}}\xspace{\mathsf{To}}$ install damping Rate Extension cable needs making holes to panel or speaker board.

 $\label{eq:spring_type_spring$

%Please see our website <u>http://www.blitz.co.jp/products/suspension/damper_zz-r.html</u> for more details.

Now On Sale!

http://www.blitz.co.jp/