

Additional Application



- Mono tube type shock absorber is used for all lineup:
Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.
- Damping rates are 32-way adjustable for both front and rear:
Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
- High Durability is achieved:
Red anodized, forged aluminum upper mounts, matt black painted brackets, and black chrome plated cylinder cases are used for anti-corrosion performance. To extend the life of the pillow ball, bearings type upper seats are used for strut type applications..
- Can be overhauled:
DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information

Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code
SUZUKI							
SWIFT	2004/11- 2010/09	ZC11S,ZD11S	M13A	¥165,900	¥158,000	92775	4959094927754
		ZC21S,ZD21S	M15A				
	2007/05- 2010/09	ZC71S	K12B				

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice.

Product Information

Vehicle	Model	Set Spring		Adjustable Range		Remarks	Code No.
		Front	Rear	Front	Rear		
SUZUKI							
SWIFT	ZC11S,ZD11S ZC21S,ZD21S ZC71S	5.0k 200mm ST	4.0k 180mm BS	-75~0	-60~-25	100mm Extension Cable	92775

Adjustable Range may be different depending on the vehicle.

Set Spring ... kgf/mm

※To install the Damping Rate Extension Cable, you may need to make holes in the panel or the speaker board.

※Spring Type 「ST: Straight Spring ID62 」 「BS: Barrel Type or Taper Type」 for Exclusive Spring.

※Please see our website http://www.blitz.co.jp/products/suspension/damper_zz-r.html for more details.