## BL/TZ INFORMATION

No. 2013-0077EN 2013/8/23 Blitz Co., Ltd.

## Additional Application



- Mono tube type shock absorber is used for all lineup: Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.
- Damping rates are 32-way adjustable for both front and rear:
  Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
- Can be overhauled:

DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information										
Vehicle	Model Year	Model	Model E/G Model		SRP w/tax MSRP		JAN Code			
BMW	ļ									
MINI COOPER S PACEMAN (R61)	2013/03-	DBA-SS16S	_	¥165,900	¥158,000	92450	4959094924500			

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice.

Product Information												
		Spring		Adjustable Range								
Vehicle	Model	Front	Rear	Front	Rear	Remarks	Code No.					
BMW		ļ.										
MINI COOPER S PACEMAN (R61)	DBA-SS16S	7.0k 160mm BS	8.0k 200mm ST	-75~-10	-50~0	w/250mm Damping Rate Extension Cable	92450					

To install the Damping Rate Extension Cable, you may need to make holes in the panel or the speaker board.
 Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.
 Adjustable Range may be different depending on the vehicle.
 Set Spring ··· kgf/mm

%Please see our website <u>http://www.blitz.co.jp/products/suspension/damper\_zz-r.html</u> for more details.

http://www.blitz.co.jp/