## BL/TZ INFORMATION

No. 2013-0103EN 2013/10/11 Blitz Co., Ltd.

## **New Product Information**



- Mono tube type shock absorber is used for all lineup:
   Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.
- Damping rates are 32-way adjustable for both front and rear:
   Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
- High Durability is achieved:
   Red anodized, forged aluminum upper mounts, matt black painted brackets, and black chrome plated cylinder cases are used for anti-corrosion performance. To extend the life of the pillow ball, bearings type upper seats are used for strut type applications..
- Can be overhauled:
   DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information											
Vehicle	Model Year	lel Year Model E/G Model		MSRP w/tax MSRP		Code No.	JAN Code				
NISSAN											
NOTE	2012/09-	E12	HR12DE, HR12DDR	¥165,900	¥158,000	92493	4959094924937				

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice.

Product Information											
Vehicle	Model	Spring		Adjustable Range							
		Front	Rear	Front	Rear	Remarks	Code No.				
NISSAN	'		•								
		5.0k	4.5k								
NOTE	E12	180mm	190mm	-50 <b>~</b> 0	-60 <b>~</b> -15		92493				
		ST	BS								

Adjustable Range may be different depending on the vehicle.

Set Spring · · · kgf/mm

\*To install the Damping Rate Extension Cable, you may need to make holes in the panel or the speaker board.

\*\*Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.

\*\*Please see our website http://www.blitz.co.jp/products/suspension/damper\_zz-r.html for more details.

Release Date: On Sale Now!