BL/TZ INFORMATION

No. 2013-0117EN 2013/12/27 Blitz Co., Ltd.

New Product Information



- Mono tube type shock absorber is used for all lineup:
 - Low friction, large 44mm diameter piston quickly responds to the input for initial damping to achieve the comfortable ride and controllability.
- Damping rates are 32-way adjustable for both front and rear: Wide adjustability results in the high balance of the driving performance and ride comfort, from the street to the circuit.
- Can be overhauled:
 - DAMPER ZZ-R can be overhauled even though priced low. Since the damper wears out over the time, the original performance of the damper can be recovered by overhauling.

Vehicle Information											
Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code				
MAZDA			1	I							
CX-5		KEEFW	PE-VPS	¥165,900	¥158,000	92498	4959094924982				
		KEEAW	PE-VPS								
		KE2FW	SH-VPTS								
		KE2AW	SH-VPTS								
BMW											
116i (F20)	2011/09-	DBA-1A16	N13B16A	V170 400	V160 000	00400	4050004004001				
120i (F20)	2011/09-	DBA-1A16	N13B16A	¥176,400	¥168,000	92482	4959094924821				
320i (F30)	2012/04-	DBA-3B20	N20B20B		¥168,000	92483	4959094924838				
328i (F30)	2012/01-	DBA-3A20	N20B20A	V170 400							
320i TOURING (F31)	2012/12-	DBA-3B20	N20B20A	¥176,400							
328i TOURING (F31)	2012/09-	DBA-3A20	N20B20A	1							

Product and price are might be modified for improvement without notice, also, above setting vehicle will discontinue without notice.

Product Information												
Vehicle		Spring		Adjustable Range								
	Model	Front	Rear	Front	Rear	Remarks	Code No.					
MAZDA			•	'		•	,					
CX-5	KEEFW KEEAW KE2FW KE2AW	6.0k 220mm ST	4.3k 258mm BS	-90~0	-75 ~ -37	Confirmed both 2WD and 4WD model	92498					
BMW												
116i(F20) 120i(F20)	DBA-1A16	6.0k 180mm BS	8.0k 220mm ST	-65 ~ 0	-55~-15	NOT confirmed on M135i	92482					
320i(F30) 328i(F30)	DBA-3B20 DBA-3A20	6.0k 180mm BS	12.0k 220mm ST	-75 ~ 0	-55~-15	Electronic Control Damper model is NOT confirmed	92483					

Adjustable Range may be different depending on the vehicle.

Set Spring · · · kgf/mm

*To install the Damping Rate Extension Cable, you may need to make holes in the panel or the speaker board.

**Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.

**Please see our website http://www.blitz.co.jp/products/suspension/damper_zz-r.html for more details.

Release Date: Now On Sale!