## BL/TZ INFORMATION

No. 2014-0061EN 2014/5/22 Blitz Co., Ltd.

## New Product Information



- Mono tube type shock absorber is used throughout the range.: A low friction, large 44mm diameter piston quickly responds to inputs for initial damping, allowing a comfortable ride with excellent controllability.
- Damping rates are 32-way adjustable for both front and rear:
  Wide adjustability results in a high balance of driving performance and ride comfort, from the street to the circuit.
- Can be overhauled: DAMPER ZZ-R is low priced, but can still be overhauled. Dampers wear out over time, but original performance can be restored by overhauling.

| 適合車種情報            |            |               |           |            |          |          |               |  |  |  |  |
|-------------------|------------|---------------|-----------|------------|----------|----------|---------------|--|--|--|--|
| Vehicle<br>TOYOTA | Model Year | Model         | E/G Model | MSRP w/tax | MSRP     | Code No. | JAN Code      |  |  |  |  |
| νοχγ              | 2014/01-   | ZRR80G,ZRR80W | 3ZR-FAE   |            | ¥158,000 | 92318    | 4959094923183 |  |  |  |  |
|                   |            | ZRR85G,ZRR85W | 3ZR-FAE   | X170.040   |          |          |               |  |  |  |  |
|                   | 2014/02-   | ZWR80G        | 2ZR-FXE   |            |          |          |               |  |  |  |  |
| NOAH              | 2014/01-   | ZRR80G,ZRR80W | 3ZR-FAE   | ¥170,640   |          |          |               |  |  |  |  |
|                   |            | ZRR85G,ZRR85W | 3ZR-FAE   |            |          |          |               |  |  |  |  |
|                   | 2014/02-   | ZWR80G        | 2ZR-FXE   |            |          |          |               |  |  |  |  |

Product and price might be modified for improvement without notice. Vehicle settings can be discontinued without notice.

| Product Information<br>Spring Adjustable Range |                            |                     |                     |        |          |         |          |  |  |  |  |
|--|----------------------------|---------------------|---------------------|--------|----------|---------|----------|--|--|--|--|
| Vehicle  | Model                      | Front               | Rear                | Front  | Rear     | Remarks | Code No. |  |  |  |  |
| ΤΟΥΟΤΑ   |                            | ļ                   | l                   |        |          |         |          |  |  |  |  |
| VOXY<br>NOAH                                   | ZRR80G<br>ZRR80W<br>ZWR80G | 6.0k<br>220mm<br>ST | 5.5k<br>215mm<br>BS | -90~0  | -65~-15  |         | 92318    |  |  |  |  |
| VOXY<br>NOAH                                   | ZRR85G<br>ZRR85W           | 6.0k<br>220mm<br>ST | 5.5k<br>215mm<br>BS | -100~0 | -100~-50 |         | 92318    |  |  |  |  |

Adjustable Range may be different depending on the vehicle.

Set Spring •••• kgf/mm

Spring Type 「ST: Straight Spring ID62 」「BS: Barrel Type or Taper Type」 for Exclusive Spring.

%Please see our website http://www.blitz.co.jp/products/suspension/damper\_zz-r.html for more details.

Release Date : On Sale Now!

http://www.blitz.co.jp/