

Additional Application



| Vehicle | Model Year | Model | E/G Model | MSRP w/tax | MSRP | Code No. | JAN Code |
|--------------|------------|-------------------|--------------------|------------|----------|----------|---------------|
| MAZDA | | | | | | | |
| ATENZA WAGON | 2015/01- | GJEFW,GJ5FW,GJ2FW | PE-VPR, | ¥170,640 | ¥158,000 | 92316 | 4959094923169 |
| ATENZA SEDAN | | GJEFP,GJ5FP,GJ2FP | SH-VPTR, PY-VPR | | | | |



Product may be different from image

| Product Specification | | |
|-----------------------|-------------------------|-------------------------|
| | Front | Rear |
| Damping Rate | 32 Way | 32 Way |
| Upper Mount | Reinforced Rubber Mount | Reinforced Rubber Mount |
| Spring Rate kgf/mm | 7.0 | 4.3 |
| Spring mm | 220 | 230 |
| Spring Type ※ | ST | BS |
| Adjustable Range mm | -70~0 | -65~-30 |
| Remarks | - | |

※Spring Type 「ST: Straight Spring ID62 」
「BS: Barrel Type or Taper Type」 for Exclusive Spring

.※Adjustable Range may be different depending on the vehicle.

●Damping rate adjuster of rear side is located inside the wheel house, therefore, wheel needs to take out in order to adjust the damping rate.