

## New Product Information



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

| Vehicle              | Model Year | Model | E/G Model | MSRP w/tax | MSRP     | Code No. | JAN Code      |
|----------------------|------------|-------|-----------|------------|----------|----------|---------------|
| <b>HONDA</b>         |            |       |           |            |          |          |               |
| STEPWGN SPADA HYBRID | 2017/09-   | RP5   | LFA-H4    | ¥167,400   | ¥155,000 | 92500    | 4959094925002 |



Front: -40mm Down / Rear: -45mm Down



| Product Specification        |                         |                   |
|------------------------------|-------------------------|-------------------|
|                              | Front                   | Rear              |
| Damping Force Adjustability  | 32 Levels               | 32 Levels         |
| Length Adjustment            | ○                       | ○                 |
| Shock Absorber Structure     | Coilovers               | Separate          |
| Upright or Inverted          | Upright                 | Upright           |
| Upper Mount                  | Reinforced Rubber       | Reinforced Rubber |
| Spring Rate kgf/mm           | 5.0                     | 9.5               |
| Free Length of Spring mm     | 220                     | 180               |
| Spring Type※                 | BS                      | BS                |
| Ride Height Adjustability mm | -100 ~ 0                | -74 ~ -30         |
| Remarks                      | Specifically for HYBRID |                   |

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Release Date: On Sale Now!

<http://www.blitz.co.jp/>

## Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

| 確認車両データ<br>(Information on Verification Test Vehicle) |   |   |
|---|---|---|
| 車名/型式/グレード<br>(Vehicle Name/Model/Grade)              | STEPWGN SPADA / RP5 / HYBRID G・EX Honda SENSING |   |
|   | フロント<br>(Front)                                 | リア<br>(Rear)  |
| 車重[kg]<br>(Vehicle Weight)                            | 1030  | 790   |
| レバー比<br>(Lever Ratio)                                 | 1.0   | ショック:0.9    スプリング:1.1<br>(Shock Absorber)    (Spring) |
| タイヤサイズ<br>(Tire Size)                                 | 225/35 R19                                      |   |
| ホイールサイズ<br>(Wheel Size)                               | 19インチ × 7.5J インセット 50<br>(INCHES)    (INSET)    | 19インチ × 7.5J インセット 44<br>(INCHES)    (INSET)          |
| スプリングデータ<br>(Spring Data)                             |   |   |
| スプリングバネレート[kgf/mm]<br>(Spring Rate)                   | 5.0   | 9.5   |
| スプリング自由長[mm]<br>(Free Length of Spring)               | 220   | 180   |
| スプリング内径【】は外径<br>(Spring Inner Diameter 【Outer】)       | φ 62 - (φ 115) - φ 62                           | φ 80 - (φ 115) - φ 62.5                               |
| アライメントデータ<br>(Alignment Data)                         |   |   |
| トー [純正值]<br>(Toe [Stock Measurements])                | +0° 01' [0.0 ± 2.0mm]                           | +0° 11' [3.0 ± 3.0mm]                                 |
| キャンバー [純正值]<br>(Camber [Stock Measurements])          | -0° 49' [+0° 00' ± 0° 45']                      | -1° 19' [-1° 30' ± 0° 45']                            |
| キャスター [純正值]<br>(Caster [Stock Measurements])          | -5° 19' [-5° 00' ± 1° 00']                      | -   |
| 車高データ<br>(Vehicle Height Data)                        |   |   |
| 地面～フェンダー[mm]<br>(Ground～Fender [mm])                  | 662   | 659   |
| 純正からのダウン量[mm]<br>(Difference from Stock [mm])         | -40   | -45   |
| 車高調整範囲[mm]<br>(Ride Height Adjustability [mm])        | -100 ~ 0  | -74 ~ -30   |
| 減衰力データ<br>(Damping Force Data)                        |   |   |
| 開発時減衰力<br>(Damping Force during Development)          | 16  | 20  |

### ■Precautions During Installation

- The rear damping force adjustment dials are located inside the rear service panel.

### ■Additional Remarks

- Vehicle roll is controlled to improve cornering performance as well as ride comfort.
- Stylish form can be achieved by lowering the vehicle height.
- Passengers in the 2<sup>nd</sup> and 3<sup>rd</sup> row seats will experience a significantly smoother and relaxed ride.