

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

Vehicle	Model Year	Model	E/G Model	MSRP w/tax	MSRP	Code No.	JAN Code
SUZUKI							
SWIFT	2017/07-	ZC43S	K12C	¥148,000	¥159,840	92394	4959094923947
BALENO	2018/05-	WB42S	K10C				



Actual product will slightly vary.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Stock
Spring Rate kgf/mm	5.0	3.0
Free Length of Spring mm	170	155
Spring Type※	ST	BS
Ride Height Adjustability mm	-90~0	-44~-14
Remarks	Includes 250mm extension dials.	

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- Remove the service panel in order to make adjustments to the rear damping force.
- The data on ride height adjustability has been taken from ZC33S.

■Additional Remarks

- Vehicle roll is limited to improve cornering performance.
- By lowering the vehicle, stylish form can be achieved.
- Stability on the highway can be improved by increasing the damping force.
- With 32 levels of damping force adjustability, optimal settings for different types of road conditions can be made.