

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

| (Vehicle) | (Model Year) | (Model) | (E/G Model) | (MSRP w/tax) | (MSRP) | (Code No.) | (JAN Code) |
|--------------|--------------|----------------------------|--------------------|--------------|----------|------------|---------------|
| MAZDA | | | | | | | |
| CX-3 | 18/07- | DK8FW,DK8AW DKEFW,DKEAW | S8-DPTS, PE-VPS | ¥176,040 | ¥163,000 | 92346 | 4959094923466 |



Actual product may slightly vary.

| Product Specification | | |
|------------------------------|--------------------|-------------------|
| | Front | Rear |
| Damping Force Adjustability | 32 Levels | 32 Levels |
| Length Adjustment | ○ | ○ |
| Shock Absorber Structure | Coilovers | Separate |
| Upright or Inverted | Upright | Upright |
| Upper Mount | Reinforced Rubber | Reinforced Rubber |
| Spring Rate kgf/mm | 5.0 | 4.0 |
| Free Length of Spring mm | 220 | 190 |
| Spring Type※ | ST | BS |
| Ride Height Adjustability mm | -85~0 | -59~-23 |
| Remarks | 2WD/4WD Compatible | |

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- Since the rear damping force adjustment dials are located inside the wheel well, the wheels must be removed in order to make adjustments.
- The data on ride height adjustability has been taken from DK5A.

■Additional Remarks

- Cornering performance can be improved by lowering the center of gravity.
- By lowering the vehicle, stylish form can be achieved.
- Increase the damping force to improve stability at high speeds.