BL/TZ INFORMATION

No. 2018-0237 2018/7/31 Blitz Co., Ltd.

Additional Applications



■With a core thickness of 42mm, the capacity has been greatly increased.

Heat dissipation has been improved by redesigning the outer fin.

Water sensor can be installed in the 1/8PT service hole.

Even at a reasonable price, the tank has a high quality buffed finish.

■Includes alumite drain bolt and BLITZ original radiator cap.

%Precautions during installation for 86 GR

Compared to stock, this product has a significantly thicker tank and core.

Therefore the radiator shroud must be cut and modified for proper installation.

For more details please contact the support center.



18867



Installation example on 86GR

Information on Compatible Vehicles							
(Manufacturer)	(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Remarks)		
ΤΟΥΟΤΑ	86 GR	17/12-	ZN6	FA20	MT/AT Compatible		

Product Information						
(Product Name)	(MSRP)	(Code No.)	(JAN Code)			
RACING RADIATOR type ZS	¥ 42,000	18867	4959094188674			

Further Details						
	(Capacity)	(Core Thickness)	(Tank Thickness)			
Stock	Roughly 0.7L	16mm	25mm			
RACING RADIATOR type ZS	Roughly 3.0L	42mm	55mm			

http://www.blitz.co.jp/