BL/TZ INFORMATION

No. 2018-0315 2018/10/17 Blitz Co., Ltd.

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
BMW MINI							
MINI JOHN COOPER WORKS		XRJCWM (F56)					
MINI JOHN COOPER WORKS CONVERTIBLE	18/05-	WJJCWM (F57)	B48A20B	¥181,440	¥168,000	92323	4959094923237



Α	C	tual	proc	luct	may	slig	htly	vary.
---	---	------	------	------	-----	------	------	-------

Product Specification						
	Front	Rear				
Damping Force Adjustability	32 Levels	32 Levels				
Length Adjustment	0	0				
Shock Absorber Structure	Coilovers	Separate				
Upright or Inverted	Upright	Upright				
Upper Mount	Stock	Stock				
Spring Rate kgf/mm	6.0	5.0				
Free Length of Spring mm	180	150				
Spring Type※	BS	BS				
Ride Height Adjustability mm	-85 ~ 0	-65 ~ -30				
	Rear damping force dials are					
D 1	located inside the wheel well.					
Remarks	Specifically for vehicles without					
	Dynamic Damper Control.					

- *Abbreviation for Spring Types \[ST: ID62 Straight Spring \], \[\in BS: Barrel or Tapered, Vehicle Specific Springs \]
- XAdjustability in ride height may vary between vehicles.
- Precautions During Installation
 - Rear damping force adjustment dials are located inside the wheel well. Therefore the wheels must be removed in order to make adjustments.
 - Specifically for vehicles without Dynamic Damper Control.
 - This product includes 4 wheels spacers (5mm thick).

Please use the spacers if the wheels or tires have a possibility of coming in contact with the shock absorbers.

- Other Remarks
 - Data on vehicle ride height adjustability has been take from XM15.
 - Lower your vehicle for a stylish form.
 - ■Cornering performance is enhanced by limiting vehicle roll.