

New Product Information



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
HIACE	04/08-	TRH200V(K) TRH211K, KDH200V(K), KDH201V(K), GDH201V, GDH211K	1TR-FE, 2KD-FTV, 1KD-FTV, 1GD-FTV	¥192,240	¥178,000	92514	4959094925149



Front : -38mmDown / Rear : -40mmDown

※Front ride height is adjusted by the torsion bar.



Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Separate	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Height Adjustment	Torsion bar	Low Down Block
Ride Height Adjustability mm	-	-40
Remarks	Low Down Block and Bump Stop are included.	

Release Date : October 19th, 2018

<http://www.blitz.co.jp/>

Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

確認車両データ (Information on Verification Test Vehicle)		
車名/型式/グレード (Vehicle Name/Model/Grade)	HIACE / TRH200V /	スーパーGL
	フロント (Front)	リア (Rear)
車重[kg] (Vehicle Weight)	1060	710
レバー比 (Lever Ratio)	-	-
タイヤサイズ (Tire Size)	225/50 R18	225/50 R18
ホイールサイズ (Wheel Size)	18インチ × 8.0J インセット 38 (INCHES) (INSET)	18インチ × 8.0J インセット 38 (INCHES) (INSET)
スプリングデータ (Spring Data)		
スプリングバネレート[kgf/mm] (Spring Rate)	トーションバー調整	ローダウンブロック
スプリング自由長[mm] (Free Length of Spring)	-	-
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	-	-
アライメントデータ (Alignment Data)		
トー [純正值] (Toe [Stock Measurements])	-° --' [2.0 ± 2.0mm]	-° --' [- ± -mm]
キャンパー [純正值] (Camber [Stock Measurements])	-° --' [-0° 20' ± 0° 30']	-° --' [-° --' ± -° --']
キャスター [純正值] (Caster [Stock Measurements])	-° --' [-2° 20' ± 0° 30']	-
車高データ (Vehicle Height Data)		
地面～フェンダー[mm] (Ground～Fender [mm])	-	-
純正からのダウン量[mm] (Difference from Stock [mm])	-38	-40
車高調整範囲[mm] (Ride Height Adjustability [mm])	-	-40
減衰力データ (Damping Force Data)		
開発時減衰力 (Damping Force during Development)	10	10

■Precautions During Installation

- Front and rear damping force adjustment dials are located inside the wheel well.
- Please make adjustments to the rear ride height by using the low down block included in the kit.

The front ride height is adjusted using the torsion bar.

※Please make sure the vehicle ride height has not changed by more than 40mm.

※Please be cautious since the vehicle ride height may be lower than the measurements listed on the vehicle inspection sheet.

■Other Remarks

- Shock absorbers, 40mm Low Down Block, Bump Stop for the front and rear are included.
- Lower your vehicle for a stylish form.
- Improve straight line stability during high speeds by increasing the damping force.