

## New Product Information



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
<b>SUBARU</b>							
LEGACY OUTBACK	14/10-	BS9	FB25	¥ 176,040-	¥ 163,000-	92509	4959094925095



Front: -38mm Down / Rear: -39mm Down

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Coilovers
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced	Reinforced
	Rubber	Rubber
Spring Rate kgf/mm	6.0	6.0
Free Length of Spring mm	200	200
Spring Type※	ST	ST
Ride Height Adjustability mm	-110 ~ 0	-60 ~ -5
Remarks	-	

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Release Date : November 7<sup>th</sup> (Wednesday)

<http://www.blitz.co.jp/>

## Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

確認車両データ (Information on Verification Test Vehicle)		
車名/型式/グレード (Vehicle Name/Model/Grade)	LEGACY OUTBACK /	BS9 / Limited
	フロント (Front)	リア (Rear)
車重[kg] (Vehicle Weight)	920	660
レバー比 (Lever Ratio)	1.0	1.1
タイヤサイズ (Tire Size)	225/60/18	225/60/18
ホイールサイズ (Wheel Size)	18インチ × 7.5J インセット 48 (INCHES) (INSET)	18インチ × 7.5J インセット 48 (INCHES) (INSET)
スプリングデータ (Spring Data)		
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	6.0
スプリング自由長[mm] (Free Length of Spring)	200	200
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	φ 62	φ 62
アライメントデータ (Alignment Data)		
トー [純正值] (Toe [Stock Measurements])	+0° 01' [0 ± 3.0mm]	+0° 09' [0 ± 3.0mm]
キャンバー [純正值] (Camber [Stock Measurements])	-0° 45' [-0° 20' ± 0° 45']	-2° 27' [-1° 35' ± 0° 45']
キャスター [純正值] (Caster [Stock Measurements])	+4° 59' [+5° 13' ± 1° 00']	-
車高データ (Vehicle Height Data)		
地面～フェンダー[mm] (Ground～Fender [mm])	743	748
純正からのダウン量[mm] (Difference from Stock [mm])	-38	-39
車高調整範囲[mm] (Ride Height Adjustability [mm])	-110 ~ 0	-60 ~ -5
減衰力データ (Damping Force Data)		
開発時減衰力 (Damping Force during Development)	22	24

### ■Precautions During Installation

- The rear damping force can be adjusted by removing the cargo room side panels.

### ■Other Remarks

- Body roll is limited to increase vehicle stability during cornering.
- Lower your vehicle for a stylish form.
- Improve straight line stability during high speeds by increasing the damping force.