

Additional Applications

OIL SENSOR ATTACHMENT



19236 Product Composition



19242 Product Composition



SUZUKI SWIFT SPORT
19236 Installation Example

- This attachment can take readings by being installed in between the stock oil filter and the engine.
- Product No.19236 TypeD includes 3/4-16 and M20-P1.5 center bolts.
- Product No.19242 TypeH includes M20-1.5 center bolts.
- The O rings fit $\phi 65$ and $\phi 70$.
- Since the ideal mounting locations for the sensors will vary between vehicles, the attachment is threaded with three 1/8 PT holes.
- The product includes two 1/8 PT tapered plugs.

※ The color of the center bolt may vary from the sample photo.

※ Does not include Oil filter, TEMP, PRESS sensors. Please purchase them separately.

| (Product Name) | (MSRP) | (Code No.) | (JAN Code) |
|-----------------------------|--------|------------|---------------|
| OIL SENSOR ATTACHMENT TypeD | ¥6,000 | 19236 | 4959094192367 |
| OIL SENSOR ATTACHMENT TypeH | ¥9,000 | 19242 | 4959094192428 |

Information on Compatible Vehicles.

| (Vehicle) | (Model Year) | (Model) | (E/G Model) | (Center Bolt) | (O-Ring Size) | (Code No.) |
|---------------|--------------|---------|-------------|---------------|---------------|--------------|
| HONDA | | | | | | |
| CIVIC TYPE R | 17/09- | FK8 | K20C | M20-P1.5 | $\phi 65$ | 19242 |
| SUZUKI | | | | | | |
| SWIFT SPORT | 17/09- | ZC33S | K14C | 3/4-16 | $\phi 65$ | 19236 |