

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MAZDA							
MAZDA6 SEDAN	19/08-	GJEFP,GJ2FP GJ5FP,GJ2AP	PE-VPR,SH-VPTR PY-RPR,PY-VPTS	¥178,200	¥165,000	92316	4959094923169
MAZDA6 WAGON		GJEFW,GJ2FW GJ5FW,GJ2AW					



Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	7.0	4.3
Free Length of Spring mm	220	230
Spring Type※	ST	BS
Ride Height Adjustability mm	-70 ~ 0	-65 ~ -30
Remarks	Rear damping force adjustment dials are located inside the wheel well	

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- Rear damping force adjustment dials are located inside the wheel well. In order to make adjustments the wheels must be removed.
- Data on ride height adjustability has been taken from GJ2FP.

■Other Remarks

- Cornering performance has been improved by limiting vehicle roll.
- Lower your vehicle for a stylish look.