## BL/TZ INFORMATION

No. 2019-0277 2019/9/20 Blitz Co., Ltd.

## Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

| (Vehicle) | (Model Year) | (Model)     | (E/G Model)    | (MSRP w/tax) | (MSRP)   | (Code No.) | (JAN Code)    |
|-----------|--------------|-------------|----------------|--------------|----------|------------|---------------|
| MAZDA     |              |             |                |              |          |            |               |
| MAZDA2    | 19/09-       | DJLFS,DJ5FS | P5-VPS,S5-DPTS | ¥178,200     | ¥165,000 | 92339      | 4959094923398 |



| Product Specification        |                                     |            |  |  |  |  |
|------------------------------|-------------------------------------|------------|--|--|--|--|
|                              | Front                               | Rear       |  |  |  |  |
| Damping Force Adjustability  | 32 Levels                           | 32 Levels  |  |  |  |  |
| Length Adjustment            | 0                                   | 0          |  |  |  |  |
| Shock Absorber Structure     | Coilovers                           | Separate   |  |  |  |  |
| Upright or Inverted          | Upright                             | Upright    |  |  |  |  |
| Line on Marinet              | Reinforced                          | Reinforced |  |  |  |  |
| Upper Mount                  | Rubber                              | Rubber     |  |  |  |  |
| Spring Rate kgf/mm           | 5.0                                 | 2.0        |  |  |  |  |
| Free Length of Spring mm     | 200                                 | 190        |  |  |  |  |
| Spring Type※                 | ST                                  | BS         |  |  |  |  |
| Ride Height Adjustability mm | -85 ~ 0                             | -75 ~ -35  |  |  |  |  |
|                              | 2WD Specific                        |            |  |  |  |  |
| Remarks                      | Rear damping force adjustment dials |            |  |  |  |  |
|                              | are located inside the wheel well   |            |  |  |  |  |

\*\*Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」
\*\*Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- Rear damping force adjustment dials are located inside the wheel well. In order to make adjustments the wheels must be removed.
- Data on ride height adjustability has been taken from DJ5FS.

■Other Remarks

- Lower your vehicle for a stylish look.
- Cornering performance has been improved by limiting vehicle roll.
- Increase the damping force for more stability during high speeds.

## http://www.blitz.co.jp/