

## New Product Information



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
<b>TOYOTA</b>							
RAV4	19/04-	MXAA52,MXAA54 AXAH52,AXAH54	M20A-FKS, A25A-FXS	¥187,000	¥170,000	92532	4959094925323



Front :-45mm Down / Rear :-46mm Down

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.0	6.0
Free Length of Spring mm	220	230
Spring Type※	ST	BS
Ride Height Adjustability mm	-95 ~ 0	-80 ~ -30
Remarks	Rear damping force adjustment dials are located inside the wheel well.	

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Release Date: October 17<sup>th</sup>, 2019 (Thursday)

<http://www.blitz.co.jp/>

## Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

DAMPER仕様・車両情報 (DAMPER specification, vehicle information)		
スプリングデータ (Spring Data)		
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	6.0
スプリング自由長[mm] (Free Length of Spring)	220	230
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	φ 62	φ 62 - (φ 115) - φ 62
減衰力データ (Damping Force Data)		
減衰力調整 [開発時減衰] (Damping force adjustment)	32 [16]	32 [16]
セッティングデータ (Damping Force Data)		
地面～フェンダー[mm] (Ground～Fender [mm])	760	755
純正からのダウン量[mm] (Difference from Stock [mm])	-45	-46
最大車高調整範囲[mm] (Maximum height adjustment range [mm])	-95 ~ 0	-80 ~ -30
レバー比 (Lever Ratio)	1.1	ショック:0.9      スプリング:1.2 (Shock Absorber)      (Spring)
テスト車両情報 (Test vehicle information)		
車名/型式/グレード (Vehicle Name/Model/Grade)	RAV4	AXAH54 / HYBRID G
	フロント (Front)	リア (Rear)
車重[kg] (Vehicle Weight)	970	740
タイヤサイズ (Tire Size)	225/60 R18	225/60 R18
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 35 (INCHES) (INSET)	18インチ × 7.0J インセット 35 (INCHES) (INSET)
アライメントデータ (Alignment Data)		
トー [純正值] (Toe [Stock Measurements])	-0° 04' [2.5 ± 2.0mm]	+0° 07' [2.6 ± 2.0mm]
キャンバー [純正值] (Camber [Stock Measurements])	-1° 38' [-0° 20' ± 0° 45']	-2° 27' [-1° 05' ± 0° 45']
キャスター [純正值] (Caster [Stock Measurements])	+5° 11' [+5° 00' ± 0° 45']	-
最低地上高データ (Vehicle Height Data)		
最低地上高場所 [数値mm] (Minimum ground elevation [Numerical data mm])	マフラータイコ前側(2個目) [141mm]	

### ■Precautions During Installation

- The rear damping force adjustment dials are located inside the wheel well.  
The wheels must be removed in order to make adjustments.
- Data on ride height adjustability has been taken from AXAH54.

### ■Other Remarks

- Cornering performance has been improved by limiting vehicle roll.
- Make adjustments to the damping force depending on the number of passengers to optimize ride comfort.
- Increase the damping force for more stability during high speeds.
- Lower your vehicle for a stylish look.