

Additional Applications

OIL SENSOR ATTACHMENT



19236 TypeD Product Composition



Installation Example TOYOTA
COROLLA TOURING



Installation Example on
NISSAN SKYLINE

- This attachment can take readings by being installed in between the stock oil filter and the engine.
- Includes 3/4-16 and M20-P1.5 center bolts. The O rings fit $\phi 65$ and $\phi 70$.
- Since the ideal mounting locations for the sensors will vary between vehicles, the attachment is threaded with three 1/8 PT holes.
- The product includes two 1/8 PT tapered plugs.

※ The color of the center bolt may vary from the sample photo.

※ Does not include Oil filter, TEMP, PRESS sensors. Please purchase them separately.

Information on Compatible Vehicles.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Center Bolt)	(O-Ring Size)	(Type)
TOYOTA						
COROLLA	19/10-	NRE210	8NR-FTS	3/4-16	$\phi 65$	TypeD
COROLLA TOURING	19/10-	NRE210W	8NR-FTS	3/4-16	$\phi 65$	TypeD
NISSAN						
SKYLINE	19/09-	RV37	VR30DDTT	M20-P1.5	$\phi 65$	TypeD

Product Information

(Product Name)	(MSRP)	(Code No.)	(JAN Code)
OIL SENSOR ATTACHMENT TypeD	¥6,000	19236	4959094192367

For more information on other applications, please check the BLITZ POWER SITE listed below.

<http://www.blitz.co.jp/>