

## New Product Information



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
<b>TOYOTA</b>							
HIACE	04/08-	KDH205V(K), KDH206K, GDH206V, TRH216K, TRH219W	2KD-FTV, 1GD-FTV, 2TR-FE	¥198,000	¥180,000	92541	4959094925415



Front: -48mm Down / Rear: -39mm Down



Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Separate	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Height Adjustment	Torsion Bar	Low Down Block
Ride Height Adjustability mm	-	-40
Remarks	Includes Low Down Block and Bump Stop 4WD Specific	

※Front ride height can be adjusted using the torsion bar.

Release Date: October 31<sup>st</sup>, 2019

<http://www.blitz.co.jp/>

## Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

DAMPER仕様・車両情報 (DAMPER specification, vehicle information)		
スプリングデータ (Spring Data)		
スプリングバネレート[kgf/mm] (Spring Rate)	トーションバー調整	ローダウンブロック
スプリング自由長[mm] (Free Length of Spring)	-	-
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	-	-
減衰力データ (Damping Force Data)		
減衰力調整 [開発時減衰] (Damping force adjustment)	32 [10]	32 [10]
セッティングデータ (Damping Force Data)		
地面～フェンダー[mm] (Ground～Fender [mm])	-	-
純正からのダウン量[mm] (Difference from Stock [mm])	-49	-39
最大車高調整範囲[mm] (Maximum height adjustment range [mm])	-	-39
レバー比 (Lever Ratio)	-	-
テスト車両情報 (Test vehicle information)		
車名/型式/グレード (Vehicle Name/Model/Grade)	HIACE / GDH206V /	スーパーGL
	フロント (Front)	リア (Rear)
車重[kg] (Vehicle Weight)	1290	790
タイヤサイズ (Tire Size)	195/80 R15	195/80 R15
ホイールサイズ (Wheel Size)	15インチ × 6.0J インセット 35 (INCHES) (INSET)	15インチ × 6.0J インセット 35 (INCHES) (INSET)
アライメントデータ (Alignment Data)		
トー [純正值] (Toe [Stock Measurements])	+0° 03' [2.0 ± 2.0mm]	+0° 06' [- ± -mm]
キャンバー [純正值] (Camber [Stock Measurements])	-1° 00' [-0° 12' ± 0° 30']	-0° 02' [-° --' ± -° --']
キャスター [純正值] (Caster [Stock Measurements])	+3° 32' [-3° 30' ± 0° 30']	-
最低地上高データ (Vehicle Height Data)		
最低地上高場所 [数値mm] (Minimum ground elevation [Numerical data mm])	リアショック下部取り付け部 [122mm]	

### ■Precautions During Installation

- Front damping force adjustment dials are located inside the wheel well.
- Rear damping force adjustment dials are located on top of the shock absorbers.
- The rear ride height is adjusted using the low down block while the front utilizing the stock torsion bar.

※If used in Japan, please make sure that the vehicle has not been lowered by over 40mm from its registration data.

※Even for stock vehicles the actual ride height measurements may vary from its registration data.

### ■Other Remarks

- Shock absorbers, 40mm low down block, front/rear bump stop, front rebound stop are included in the kit.
- Lower your vehicle for a stylish form.
- Increase the damping force to limit vehicle roll and improve vehicle stability.