

## Additional Applications

# OIL SENSOR ATTACHMENT



19236 TypeD Product Composition



NISSAN GT-R  
Installation Example

- This attachment can take readings by being installed in between the stock oil filter and the engine.
- Includes 3/4-16 and M20-P1.5 center bolts. The O rings fit  $\phi 65$  and  $\phi 70$ .
- Since the ideal mounting locations for the sensors will vary between vehicles, the attachment is threaded with three 1/8 PT holes.
- The product includes two 1/8 PT tapered plugs.
  - ※ The color of the center bolt may vary from the sample photo.
  - ※ Does not include Oil filter, TEMP, PRESS sensors. Please purchase them separately.

### Information on Compatible Vehicles

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Center Bolt)	(O-Ring Size)	(Type)
NISSAN						
GT-R	07/12-	R35	VR38DETT	M20-P1.5	$\phi 65$	TypeD
MAZDA						
CX-30	19/10-	DM8P	S8-DPTS	3/4-16	$\phi 70$	TypeD
MAZDA3 FASTBACK	19/05-	BP8P	S8-DPTS	3/4-16	$\phi 70$	TypeD
MAZDA3 SEDAN	19/05-	BP8P	S8-DPTS	3/4-16	$\phi 70$	TypeD

### Product Information

(Product Name)	(MSRP)	(Code No.)	(JAN Code)
OIL SENSOR ATTACHMENT TypeD	¥6,000	19236	4959094192367

For more information on other applications, please check the BLITZ POWER SITE listed below.

<http://www.blitz.co.jp/>