

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

| (Vehicle) | (Model Year) | (Model) | (E/G Model) | (MSRP w/tax) | (MSRP) | (Code No.) | (JAN Code) |
|---------------|--------------|---------|-------------|--------------|----------|------------|---------------|
| HONDA | | | | | | | |
| FREED | 19/10- | GB5 | L15B | ¥165,000 | ¥150,000 | 92378 | 4959094923787 |
| FREED HYBRID | | GB7 | LEB | | | | |
| FREED+ | | GB5 | L15B | | | | |
| FREED+ HYBRID | | GB7 | LEB | | | | |



| Product Specification | | |
|------------------------------|-----------|-----------|
| | Front | Rear |
| Damping Force Adjustability | 32 Levels | 32 Levels |
| Length Adjustment | ○ | ○ |
| Shock Absorber Structure | Coilovers | Separate |
| Upright or Inverted | Upright | Upright |
| Upper Mount | Stock | Stock |
| Spring Rate kgf/mm | 6.0 | 4.0 |
| Free Length of Spring mm | 200 | 200 |
| Spring Type※ | ST | BS |
| Ride Height Adjustability mm | -85 ~ 0 | -59 ~ -22 |
| Remarks | 2WD Only | |

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- The front damping force adjustment dials can be accessed by removing the service panels.
- The rear service panels must be removed or modified in order to install the rear dials.
- Data on ride height adjustment from GB7 FREED+ HYBRID.

■Other Remarks

- Cornering performance has been improved by limiting vehicle role.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.