BL/TZ INFORMATION

No.2020-0064 2020/3/19 Blitz Co., Ltd.

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MITSUBISHI							
ECLIPSE CROSS	19/06-	GK9W	4N14	¥181,500	¥165,000	92506	4959094925064







Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Coilovers			
Upright or Inverted	Upright	Upright			
Linnar Maunt	Reinforced	Reinforced			
Upper Mount	Rubber	Rubber			
Spring Rate kgf/mm	6.0	6.0			
Free Length of Spring mm	220	200			
Spring Type	ST	BS			
Ride Height Adjustability mm	-95 ~ 0	-70 ~ -15			
Remarks		-			

^{**}Abbreviation for Spring Types \[\Gamma ST: ID62 \] Straight Spring \[\J, \Gamma BS: Barrel or Tapered, Vehicle Specific Springs \] \[\XAdjustability in ride height may vary between vehicles.

BL/TZ INFORMATION

Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

	DAMPER仕様·車両情報				
(DAMPER specification, vehicle information				
	スプリングデータ (Spring Data)				
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	6.0			
スプリング自由長[mm] (Free Length of Spring)	220	200			
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	φ 65.5 – φ 62.5			
	減衰カデータ (Damping Force Data)				
減衰力調整 〔開発時減衰〕 (Damping force adjustment	32 (20)	32 [24]			
	セッティングデータ (Damping Force Data)				
地面~フェンダー[mm] (Ground~Fender [mm])	716	720			
純正からのダウン量[mm] (Difference from Stock [mm])	-40	-38			
最大車高調整範囲(mm) (Maximum height adjustment range (mm))	−95 ~ 0	-70 ~ -15			
レバー比 (Lever Ratio)	1.0	1.2			
	テスト車両情報 (Test vehicle information)				
車名/型式/グレード (Vehicle Name/Model/Grade)	ECLIPSE CROSS / GK	9W / BLACK EDITION			
	フロント (Front)	0			
車 重[kg] (Vehicle Weight)	950	730			
タイヤサイズ (Tire Size)	225/55 R18	225/55 R18			
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 38 (INCHES) (INSET)	18インチ × 7.0J インセット 38 (INCHES) (INSET)			
	アライメントデータ (Alignment Data)				
トー 〔純正値〕 (Toe [Stock Measurements])	-0° 03'[1.0 ± 2.0mm]	+0° 05' (3.0 ± 2.0mm)			
キャンバー 〔純正値〕 (Camber [Stock Measurements])	-2° 21' [+0° 15' ± 0° 30']	-2° 39' [-0° 40' ± 0° 45']			
キャスター 〔純正値〕 (Caster [Stock Measurements])	+2° 40' [+2° 30' ± 0° 45']	-			
	最低地上高データ (Vehicle Height Data)				
最低地上高場所 〔数值mm〕 (Minimum ground elevation 〔Numerical data mm〕)	2個目マフラータイコ中央 〔131mm〕				

■Precautions During Installation

•In order to install the rear damping force extension dials, the metal body panels must be drilled and modified.

Without proper modification, the suspension must be uninstalled in order to access the damping force adjustment dials.

■Other Remarks

- •Compatibility for the diesel engine model has been confirmed.
- •Cornering performance has been improved by limiting vehicle role.
- •Lower your vehicle for a stylish look.
- •Increase the damping force to improve vehicle stability during high speeds.