

Additional Applications

OIL SENSOR ATTACHMENT



19236 TypeD Product Composition



19242 TypeH Product



HONDA FIT
19242 Installation Example

- This attachment can take readings by being installed in between the stock oil filter and the engine.
 - Product No.19236 TypeD includes 3/4-16 and M20-P1.5 center bolts.
 - Product No.19242 TypeH includes M20-1.5 center bolts.
 - The O rings fit $\phi 65$ and $\phi 70$.
 - Since the ideal mounting locations for the sensors will vary between vehicles, the attachment is threaded with three 1/8 PT holes.
 - The product includes two 1/8 PT tapered plugs.
- ※ The color of the center bolt may vary from the sample photo.
※ Does not include Oil filter, TEMP, PRESS sensors. Please purchase them separately.

Information on Compatible Vehicles

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Center Bolt)	(O-Ring Size)	(Type)
TOYOTA						
COROLLA	19/10-	ZWE211, ZWE214	2ZR-FXE	3/4-16	$\phi 65$	TypeD
COROLLA SPORT	18/06-	ZWE211H	2ZR-FXE	3/4-16	$\phi 65$	TypeD
COROLLA TOURING	19/10-	ZWE211W, ZWE214W	2ZR-FXE	3/4-16	$\phi 65$	TypeD
HONDA						
FIT	20/02-	GR3, GR4, GR6, GR8	LEB	M20-P1.5	$\phi 65$	TypeH

(Product Name)	(MSRP)	(Code No.)	(JAN Code)
OIL SENSOR ATTACHMENT TypeD	¥6,000	19236	4959094192367
OIL SENSOR ATTACHMENT TypeH	¥9,000	19242	4959094192428

For more information on other applications, please check the BLITZ POWER SITE listed below.

<http://www.blitz.co.jp/>