

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MAZDA							
CX-30	19/10-	DM8P	S8-DPTS	¥181,500	¥165,000	92544	4959094925446



Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coil-overs	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.0	5.0
Free Length of Spring mm	200	205
Spring Type※	BS	BS
Ride Height Adjustability mm	-50 ~ -5	-65 ~ -30
Remarks	2WD/4WD Compatible	

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

■Precautions During Installation

- Rear damping force adjustment dials are located inside the wheel well.
Therefore the wheels must be removed in order to make adjustments.
- Data on ride height adjustability from DM8P (4WD).

■Other Remarks

- Compatibility of DM8P (2WD) has been tested.
- Cornering performance has been improved by limiting vehicle role.
- Make adjustments to the damping force depending on the number of passengers and road conditions for optimal ride quality.
- Increase the damping force to improve vehicle stability during high speeds.