BL/TZ INFORMATION

No.2020-0217 2020/8/5 Blitz Co., Ltd.

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
HARRIER HYBRID	20/06-	AXUH80	A25A-FXS	¥187,000	¥170,000	92532	4959094925323



Product Specification						
	Front	Rear				
Damping Force Adjustability	32 Levels	32 Levels				
Length Adjustment	0	0				
Shock Absorber Structure	Coilovers	Separate				
Upright or Inverted	Upright	Upright				
Linnar Maunt	Reinforced	Reinforced				
Upper Mount	Rubber	Rubber				
Spring Rate kgf/mm	6.0	6.0				
Free Length of Spring mm	220	230				
Spring Type※	ST	BS				
Ride Height Adjustability mm	-95 ~ 0	-80 ~ -35				
Remarks	2WD Hybrid					

- *Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」
- XAdjustability in ride height may vary between vehicles.

BL/TZ INFORMATION

Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

(D	DAMPER仕様・車両情報	,					
(DAMPER specification, vehicle information) スプリングデータ							
	(Spring Data)						
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	6.0					
スプリング自由長[mm] (Free Length of Spring)	220	230					
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	φ 62 – (φ 115) – φ 62					
	減衰カデータ (Damping Force Data)						
減衰力調整 〔開発時減衰〕 (Damping force adjustment	32 [16]	32 [16]					
	セッティングデータ (Damping Force Data)						
地面~フェンダー[mm] (Ground~Fender [mm])	757	760					
純正からのダウン量(mm) (Difference from Stock [mm])	-52	-59					
最大車高調整範囲〔mm〕 (Maximum height adjustment range	-95 ~ 0	-80 ~ −35					
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.2 (Shock Absorber) (Spring)					
(2010) (1000)	テスト車両情報 (Test vehicle information)						
車名/型式/グレード (Vehicle Name/Model/Grade)	HARRIER HYBRID / AXU	IH80 / S					
	フロント (Front)	リア (Rear)					
車 重[kg] (Vehicle Weight)	960	660					
タイヤサイズ (Tire Size)	225/65 R17	225/65 R17					
ホイールサイズ (Wheel Size)	17インチ × 7.0J インセット 35 (INCHES) (INSET)	17インチ × 7.0J インセット 35 (INCHES) (INSET)					
(アライメントデータ (Alignment Data)						
トー 〔純正値〕 (Toe [Stock Measurements])	+0° 04' [2.5 ± 2.0mm]	+0° 01' (2.6 ± 2.0mm)					
キャンバー 〔純正値〕 (Camber 〔Stock Measurements〕)	-2° 01' [-0° 20' ± 0° 45']	-2° 31' [-1° 05' ± 0° 45']					
キャスター 〔純正値〕 (Caster [Stock Measurements])	+5° 06' [+5° 00' ± 0° 45']	-					
, sasto. (Stock mound official)		最低地上高データ (Vehicle Height Data)					
最低地上高場所 〔数値mm〕 (Minimum ground elevation 〔Numerical data mm〕)	Minimum ground elevation 中間タイコ前側 〔140mm〕						

■Precautions During Installation

- Compatibility for AXUH80 (Hybrid) 2WD models have been confirmed.
- Rear damping force adjustment dials are located inside the wheel well.

Therefore the wheels must be removed in order to make adjustments.

■Other Remarks

- Cornering performance has been improved by limiting vehicle role.
- For optimal ride quality make adjustments to the damping force depending on the number of passengers and road conditions.
- •Increase the damping force to improve vehicle stability during high speeds.
- ●Lower your vehicle for a stylish look.