

Additional applications for the DAMPER ZZ-R has been confirmed for the Honda Odyssey Hybrid RC4 (After MC).



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.





(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
HONDA							
ODYSSEY HYBRID	2020/11-	RC4	LFA	¥172,700	¥157,000	92315	4959094923152

Product Description

- Cornering performance has been improved by limiting vehicle role.
- Lower your vehicle for a stylish look.
- Increase the damping force to improve vehicle stability during high speeds.
- Includes vehicle specific shortened stabilizer links.

Product Specification				
	Front	Rear		
Damping Force Adjustability	32 Levels	32 Levels		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Reinforced Rubber	Reinforced Rubber		
Spring Rate kgf/mm	6.0	9.5		
Free Length of Spring mm	220	180		
Spring Type※	BS	BS		
Ride Height Adjustability mm	-90 ∼ 0	-75 ∼ -25		



■ Remarks:2WD Only

*Abbreviation for Spring Types [ST:ID62 Straight Spring], [BS:Barrel or Tapered, Vehicle Specific Springs]

XAdjustability in ride height may vary between vehicles.

Optional Parts						
Product Name	Code No.	MSRP w/tax	MSRP	Remarks		
DSC PLUS Vehicle Specific Set TYPE-H	15243	¥75,460	¥68,600	Upgrade to the DSC Plus with the vehicle specific set		



Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

		_			
DAMPER仕様 • 車両情報 (DAMPER specification, vehicle information)					
	スプリングデータ				
	(Spring Data)				
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	9.5			
スプリング自由長[mm] (Free Length of Spring)	220	180			
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62 – (φ 115) – φ 62	φ 80 – (φ 115) – φ 62.5			
	減衰力データ (Damping Force Data)				
減衰力調整 〔開発時減衰〕 (Damping force adjustment	32 (22)	32 (22)			
(Bumping 10100 adjustment	セッティングデータ (Damping Force Data)				
地面~フェンダー[mm] (Ground~Fender [mm])	682	678			
純正からのダウン量[mm] (Difference from Stock [mm])	-38	-38			
最大車高調整範囲[mm] (Maximum height adjustment range	-90 ~ 0	-70 ~ -25			
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.1 (Shock Absorber) (Spring)			
(LOVOI Hacio)	テスト車両情報 (Test vehicle information)				
車名/型式/グレード (Vehicle Name/Model/Grade)		C4 / e:HEV ABSOLUTE•EX			
(,	フロント (Front)	リア (Rear)			
車 重[kg] (Vehicle Weight)	1070	860			
タイヤサイズ (Tire Size)	225/50 R18	225/50 R18			
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 55 (INCHES) (INSET)	18インチ × 7.0J インセット 55 (INCHES) (INSET)			
,	アライメントデータ (Alignment Data)				
トー 〔純正値〕 (Toe [Stock Measurements])	-0° 02'(0.0 ± 2.0mm)	+0° 12' [2.0 +4~-2 mm]			
キャンバー 〔純正値〕 (Camber [Stock Measurements])	-1° 42' [-0° 05' ± 0° 45']	-1° 38' [-1° 45' ± 0° 45']			
キャスター 〔純正値〕 (Caster [Stock Measurements])	+5° 47' [+5° 40' ± 1° 00']	-			
(Sastor Cotoon modern emolito)	最低地上高データ (Vehicle Height Data)				
最低地上高場所 〔数值mm〕 (Minimum ground elevation 〔Numerical data mm〕)	(Venicle Height Data) リアマフラータイコ(2個目) [118mm]				

- Precautions during installation
- The front damping force adjustment dials are located below the windshield wipers. In order to make adjustments the service panel must be removed.
- Rear damping force adjustments dials are located under the interior service panels.
 Please remove the panels to make adjustments.