

Additional applications for the DAMPER ZZ-R has been confirmed for the Toyota Supra (DB02)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.





(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
SUPRA	2020/04-	DB02	B58	¥209,000	¥190,000	92550	4959094925507

Product Description

- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Lower your vehicle for a stylish look..
- The pillow ball upper mount allows you to make camber adjustments to the front suspension.
- Compatible with DSC PLUS.

Product Specification						
	Front	Rear				
Damping Force Adjustability	32 Levels	32 Levels				
Length Adjustment	0	0				
Shock Absorber Structure	Coilovers	Separate				
Upright or Inverted	Upright	Upright				
Upper Mount	Adjustable Pillow	Reinforced Rubber				
Spring Rate kgf/mm	6.0	8.0				
Free Length of Spring mm	170	260				
Spring Type※	BS	ST				
Ride Height Adjustability mm	-55 ∼ 0	-50 ∼ -5				

■ Remarks: Please purchase and install the separately sold canceller for proper use.

**Abbreviation for Spring Types 「ST: ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」

**Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	MSRP w/tax	MSRP	Remarks
DSC PLUS Vehicle Specific Set TYPE-E	15240	¥82,060	¥74,600	Upgrade to the DSC Plus with the vehicle specific set
SUSPENSION WARNING CANCELLER	15218	¥35,200	¥32,000	After removing the stock electronic suspension regulator, the vehicle check light will turn on. This product can turn the check light off.

- Precautions during installation
 - Please purchase our separately sold SUSPENSION WARNING CANCELLER, (Product Code: 15218) to turn off the vehicle check light.
 - Rear damping force adjustment dials are located inside the wheel well. Therefore the wheels must be removed in order to make adjustments.