

New applications for the DAMPER ZZ-R Lift Up Version has been confirmed for the Toyota RAV4 Hybrid (AXAH54)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit





(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
RAV4 HYBRID	2019/04-	AXAH54	A25A	¥198,000	¥180,000	92567	4959094925675

Product Description

- Damper ZZ-R Lift Up version.
- Raise the height of your vehicle for a powerful look.
- The spring rate has been refined to be comfortable even after lifting the vehicle.
- The damping force has set to maintain vehicle stability and comfort even during high speeds.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Compatible with DSC PLUS.

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	7.0	6.0			
Free Length of Spring mm	220	300			
Spring Type※	ST	BS			
Damping Force Adjustability	0 ~ +40	+5 ∼ +55			



■ Remarks: Confirmed with Hybrid 2WD. Untested with Gasoline 2WD, 4WD.

*Abbreviation for Spring Types \[ST: ID62 Straight Spring \], \[FBS: Barrel or Tapered, Vehicle Specific Springs \]

%Adjustability in ride height may vary between vehicles.

Optional Parts						
Product Name	Code No.	MSRP w/tax	MSRP	Remarks		
DSC PLUS Vehicle Specific Set TYPE-A	15236	¥66,000	¥60,000	Upgrade to the DSC Plus with the		
DSC FLOS Verlicle Specific Set 11FL-A				vehicle specific set		



Information on Verification Test Vehicle

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

DAMPER仕様·車両情報						
(DAMPER specification, vehicle information)						
	スプリングデータ					
スプリングバネレート[kgf/mm]		(Spring Data)				
(Spring Rate)	7.0	6.0				
スプリング自由長[mm]	220	300				
(Free Length of Spring)	220	300				
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	ф 62 – (ф 115) – ф 62				
(Opring Inner Diameter Couter)						
	(Damping Force Data)					
減衰力調整 〔開発時減衰〕	32 [16]	32 [16]				
(Damping force adjustment	セッティングデータ					
		mping Force Data)				
地面~フェンダー[mm]	835	830				
(Ground~Fender [mm]) 車高純正比[mm]						
平高純正氏(mm) (Difference from Stock [mm])	+32	+33				
最大車高調整範囲[mm]	0 ~ +40	+5 ~ +55				
(Maximum height adjustment range [mm])	0 1 140					
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.2 (Shock Absorber) (Spring)				
(Level Italio)	テスト車					
	アスピー学問情報 (Test vehicle information)					
車名/型式/グレード	RAV4 / AXA	.H54 / HYBRID G				
(Vehicle Name/Model/Grade)	フロント	リア				
	(Front)	(Rear)				
車 重[kg]	970	740				
(Vehicle Weight) タイヤサイズ	070	7 10				
(Tire Size)	225/60 R18	225/60 R18				
ホイールサイズ	18インチ × 7.0J インセット 35	18インチ × 7.0J インセット 35				
(Wheel Size)	(INCHES) (INSET)	(INCHES) (INSET)				
	アライメントデータ (Alignment Data)					
トー 〔純正値〕		-0° 05' [2.6 ± 2.0mm]				
(Toe [Stock Measurements])	-0° 03' (2.5 ± 2.0mm)	-0 05 [2.6 ± 2.0mm]				
キャンバー〔純正値〕	-0° 55' [-0° 20' \pm 0° 45']	-1° 11' [−1° 05' ± 0° 45']				
(Camber [Stock Measurements]) キャスター 〔純正値〕		, ,				
(Caster (Stock Measurements))	+4° 15' [+5° 00' ± 0° 45']					
	最低地上高データ					
是低种 L 古担元 (**/広)	(Vehicle Height Data)					
最低地上高場所 〔数值mm〕 (Minimum ground elevation	フロントメンバー中央 [216mm]					
[Numerical data mm])	フロフトラフィ、中久(Zionini)					

■ Precautions During Installation

- Rear damping force adjustment dials are located inside the wheel well.
- If you adjust the rear shock absorbers beyond the designated range, there is a possibility that the brake line may break.