

## Additional applications for the DAMPER ZZ-R has been confirmed for the Toyota Yaris Cross Hybrid (MXPJ15



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit





(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
YARIS CROSS HYBRID	2020/08-	MXPJ15	M15A	¥176,000	¥160,000	92572	4959094925729

## **Product Description**

- Cornering performance has been improved by limiting vehicle role.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Sufficient compression and rebound strokes have been set for optimal ride quality.
- Compatible with DSC Plus.

Product Specification				
	Front	Rear		
Damping Force Adjustability	32 Levels	32 Levels		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Stock	Stock		
Spring Rate kgf/mm	4.0	6.0		
Free Length of Spring mm	220	210		
Spring Type※	ST	BS		
Ride Height Adjustability mm	-75 ∼ 0	-40 ∼ -10		



■ Remarks: Hybrid 4WD Only. Untested with Gasoline 4WD.

\*\*Abbreviation for Spring Types \[ ST: ID62 Straight Spring \], \[ BS: Barrel or Tapered, Vehicle Specific Springs \] \*\*Adjustability in ride height may vary between vehicles.

Optional Parts						
Product Name	Code No. MSRP w/tax MSRP		MSRP	Remarks		
DSC PLUS Vehicle Specific Set TYPE-I	15244	¥75,460	¥68,600	Upgrade to the DSC Plus with the		
BOOT EOO Vernole Opcome Get 111 E 1				vehicle specific set		



## Information on Verification Test Vehicle

This product has been tested on the following vehicle. Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

DAMPER仕様·車両情報					
DAMPER TATE 中间情報 (DAMPER specification, vehicle information)					
,	スプリングデータ				
	(Spring Data)				
スプリングバネレート[kgf/mm] (Spring Rate)	4.0	6.0			
スプリング自由長[mm] (Free Length of Spring)	220	210			
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	φ 78 – (φ 105) – φ 54.5			
,	減衰力データ (Damping Force Data)				
減衰力調整 〔開発時減衰〕	32 [20]	32 [20]			
(Damping force adjustment	, ,	<>			
	セッティングデータ (Damping Force Data)				
地面~フェンダー[mm] (Ground~Fender [mm])	710	705			
純正からのダウン量(mm) (Difference from Stock [mm])	-30	-25			
最大車高調整範囲[mm] (Maximum height adjustment range	−75 <b>~</b> 0	-40 <b>~</b> −10			
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.2 (Shock Absorber) (Spring)			
(Ecvel Hadio)	テスト車両情報				
	(Test vehicle information)				
車名/型式/グレード (Vehicle Name/Model/Grade)	YARIS CROSS HYBRID / MXPJ15 / HYBRID Z				
	フロント	リア			
車 重[kg]	(Front)	(Rear)			
(Vehicle Weight)	720	550			
タイヤサイズ (Tire Size)	215/50 R18	215/50 R18			
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 50 (INCHES) (INSET)	18インチ × 7.0J インセット 50 (INCHES) (INSET)			
	アライメントデータ (Alignment Data)				
トー 〔純正値〕 (Toe [Stock Measurements])	-0° 01'[2.5 ± 2.0mm]	-0° 01'[3.6 ± 2.0mm]			
キャンバー 〔純正値〕 (Camber [Stock Measurements])	-1° 49' (-0° 05' ± 0° 45')	-1° 11' [-0° 08' ± 0° 45']			
キャスター 〔純正値〕 (Caster [Stock Measurements])	+6° 20' [+5° 51' ± 0° 45']	-			
(Suster Cotton Measurements)	最低地上高データ (Vehicle Height Deta)				
最低地上高場所 〔数值mm〕 (Minimum ground elevation 〔Numerical data mm〕)	(Vehicle Height Data) フロントメンバー中央〔142mm〕				

## ■ Precautions During Installation

- Hybrid 4WD only. Untested with Gasoline 4WD.
- Rear damping force adjustment dials can be installed without any modifications.
   However, the service panel will need to be removed before making adjustments.