

Additional applications for the DAMPER ZZ-R has been confirmed
for the MAZDA3 FASTBACK/SEDAN (SKYACTIV - X)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further details on DAMPER ZZ-R](#)



Front : -36mm Down / Rear : -43mm Down

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MAZDA							
MAZDA3 FASTBACK	2019/12-	BPEP	HF	¥181,500	¥165,000	92534	4959094925347
MAZDA3 SEDAN							

Product Description

- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Increase the damping force for greater stability during high speeds.
- Sufficient compression and rebound strokes have been set for optimal ride quality.
- Compatible with DSC Plus.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.0	5.0
Free Length of Spring mm	180	185
Spring Type※	BS	BS
Damping Force Adjustability	-55 ~ -5	-50 ~ -20



■ Remarks : Unchecked with 4WD models. Compatible with AT/MT.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	MSRP w/tax	MSRP	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	¥66,000	¥60,000	Upgrade to the DSC Plus with the vehicle specific set

Information on Verification Test Vehicle

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

DAMPER仕様・車両情報 (DAMPER specification, vehicle information)		
	スプリングデータ (Spring Data)	
スプリングバネレート[kgf/mm] (Spring Rate)	6.0	5.0
スプリング自由長[mm] (Free Length of Spring)	180	185
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	φ 62 - (φ 115) - φ 62	φ 78.5 - (φ 120) - φ 62.5
	減衰力データ (Damping Force Data)	
減衰力調整 〔開発時減衰〕 (Damping force adjustment)	32 [16]	32 [16]
	セッティングデータ (Damping Force Data)	
地面～フェンダー[mm] (Ground～Fender [mm])	652	653
基準車高[mm] (Difference from Stock [mm])	-36	-43
最大車高調整範囲[mm] (Maximum height adjustment range [mm])	-55 ～ -5	-50 ～ -20
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.1 (Shock Absorber) (Spring)
	テスト車両情報 (Test vehicle information)	
車名/型式/グレード (Vehicle Name/Model/Grade)	MAZDA3 FASTBACK / BPEP / X Burgundy Selection	
	フロント (Front)	リア (Rear)
車 重[kg] (Vehicle Weight)	910	520
タイヤサイズ (Tire Size)	215/45 R18	215/45 R18
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 45 (INCHES) (INSET)	18インチ × 7.0J インセット 45 (INCHES) (INSET)
	アライメントデータ (Alignment Data)	
トー 〔純正值〕 (Toe [Stock Measurements])	-0° 03' [1.0 ± 4.0mm]	+0° 06' [4.1 ± 5.0mm]
キャンバー 〔純正值〕 (Camber [Stock Measurements])	-0° 48' [-0° 11' ± 1° 00']	-1° 22' [-1° 29' ± 1° 00']
キャスター 〔純正值〕 (Caster [Stock Measurements])	+5° 14' [+5° 00' ± 0° 45']	-
	最低地上高データ (Vehicle Height Data)	
最低地上高場所 〔数値mm〕 (Minimum ground elevation [Numerical data mm])	リアトーションビーム下マフラーパイプ [103mm]	

■ Precautions During Installation

- Rear damping force adjustment dials are located inside the wheel well.
Therefore the wheels must be removed in order to make adjustments.