

Additional applications for the DAMPER ZZ-R has been confirmed for the Toyota Land Cruiser Prado (TRJ150W)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further details on DAMPER ZZ-R](#)



Front : +48mm (Approximately 2in) Up
Rear : +37mm(Approximately 1.5in) Up

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
LAND CRUISER PRADO	2017/09-	TRJ150W	2TR-FE	¥203,500	¥185,000	92570	4959094925705

Product Description

- Damper ZZ-R Lift Up version.
- Raise the height of your vehicle for a powerful look.
- The damping force has set to maintain vehicle stability and comfort even during high speeds.
- Headlight leveling rod included.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.

	Product Specification	
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Stock
Spring Rate kgf/mm	18.0	5.0
Free Length of Spring mm	220	310
Spring Type※	ST	BS
Ride Height Adjustability mm	+15(0.6) ~ +50(2)	+15(0.6) ~ +60(2.4)



■ Remarks : Lift up version. 2.7L gasoline.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

※() is the height different in inches.

Information on Verification Test Vehicle

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

DAMPER仕様・車両情報 (DAMPER specification, vehicle information)		
	スプリングデータ (Spring Data)	
スプリングバネレート[kgf/mm] (Spring Rate)	18.0	5.0
スプリング自由長[mm] (Free Length of Spring)	220	310
スプリング内径【】は外径 (Spring Inner Diameter 【Outer】)	φ 62	φ 119.5 - (φ 150) - φ 86
	減衰力データ (Damping Force Data)	
減衰力調整 [開発時減衰] (Damping force adjustment)	32 [16]	32 [16]
	セッティングデータ (Damping Force Data)	
地面～フェンダー[mm] (Ground～Fender [mm])	918	942
車高純正比[mm] (Difference from Stock [mm])	+48	+37
最大車高調整範囲[mm] (Maximum height adjustment range [mm])	+15 ~ +50	+15 ~ +60
レバー比 (Lever Ratio)	1.4	ショック:0.9 スプリング:1.2 (Shock Absorber) (Spring)
	テスト車両情報 (Test vehicle information)	
車名/型式/グレード (Vehicle Name/Model/Grade)	LAND CRUISER PRADO / TRJ150W / TX Lパッケージ	
	フロント (Front)	リア (Rear)
車重[kg] (Vehicle Weight)	1140	1000
タイヤサイズ (Tire Size)	265/65 R17	265/65 R17
ホイールサイズ (Wheel Size)	17インチ × 7.5J インセット 25 (INCHES) (INSET)	17インチ × 7.5J インセット 25 (INCHES) (INSET)
	アライメントデータ (Alignment Data)	
トー [純正值] (Toe [Stock Measurements])	-0° 02' [+4.08 ± 2.0mm]	-0° 08' [-. ± -.mm]
キャンバー [純正值] (Camber [Stock Measurements])	-0° 23' [+0° 22' ± 0° 30']	+0° 00' [-° --' ± -° --']
キャスター [純正值] (Caster [Stock Measurements])	+1° 33' [+2° 48' ± 0° 30']	-
	最低地上高データ (Vehicle Height Data)	
最低地上高場所 [数値mm] (Minimum ground elevation [Numerical data mm])	リアホーシング中央デフ [224mm]	

■ Precautions During Installation

- Front and rear damping force adjustment dials are located inside the wheel well.
- In order to install the rear suspension, the spare tire must be removed.