

Additional applications for the DAMPER ZZ-R has been confirmed for the Toyota Aqua (MXPK11)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit







(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
TOYOTA							
AQUA	2021/07-	MXPK11	M15A	¥165,000	¥150,000	92551	4959094925514

Product Description

- Cornering performance has been improved by lowering the center of gravity.
- Sufficient compression and rebound strokes have been set for optimal ride quality.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Compatible with DSC PLUS.

Product Specification				
	Front	Rear		
Damping Force Adjustability	0	0		
Length Adjustment	Coilovers	Separate		
Shock Absorber Structure	Upright	Upright		
Upright or Inverted	Stock	Stock		
Upper Mount	4.0	2.5		
Spring Rate kgf/mm	220	245		
Free Length of Spring mm	ST	BS		
Spring Type※	-80 ∼ 0	-60 \sim -15		
Damping Force Adjustability	Front	Rear		



■ Remarks: 2WD Only, MXPK10 unconfirmed.

**Abbreviation for Spring Types \(^{\text{ST:ID62 Straight Spring_J}}\), \(^{\text{BS:Barrel or Tapered}}\), \(^{\text{Vehicle Specific Springs_J}}\)
**Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	MSRP w/tax	MSRP	Remarks
DSC PLUS Vehicle Specific Set TYPE-I	15244	¥75,460	¥68,600	Upgrade to the DSC Plus with the vehicle specific set



Information on Verification Test Vehicle

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

	DAMPER仕様·車両情報			
(D	AMPER specification, vehicle information)			
	スプリングデータ			
スプリングバネレート[kgf/mm]	(Spring Data)			
(Spring Rate)	4.0	2.5		
スプリング自由長[mm] (Free Length of Spring)	220	245		
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	φ 80.5 – (φ 120) – φ 64.5		
(opring milot Diameter Leater)	減衰カデータ (Damping Force Data)			
減衰力調整 〔開発時減衰〕		·		
(Damping force adjustment	32 [16]	32 [16]		
	セッティングデータ (Damping Force Data)			
地面~フェンダー〔mm〕	641	640		
(Ground~Fender [mm]) 基準車高[mm]		0.0		
を手手同い回り (Difference from Stock [mm])	-27	-36		
最大車高調整範囲[mm]	-80 ~ 0	-60 ~ −15		
(Maximum height adjustment range [mm])	00 10			
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング : 1.1 (Shock Absorber) (Spring)		
(=====;	テスト車	更両情報		
	(Test vehicle information)			
車名/型式/グレード (Vehicle Name/Model/Grade)	AQUA / MXF	PK11 / Z		
(vollisie Hallie) Hiedel, di dae,	フロント	リア		
	(Front)	(Rear)		
車 重[kg] (Vehicle Weight)	750	470		
タイヤサイズ (Tire Size)	195/55 R16	195/55 R16		
ホイールサイズ	16インチ × 6.0J インセット 50	16インチ × 6.0J インセット 50		
(Wheel Size)	(INCHES) (INSET) (INCHES) (INSET) アライメントデータ			
	アライメントナータ (Alignment Data)			
├── 〔純正值〕 (Toe [Stock Measurements])	-0° 04' (0.0 ± 1.0mm)	+0° 16' [5.1 ± 3.7mm]		
キャンバー 〔純正値〕 (Camber [Stock Measurements])	-1° 51' [0° 00' ± 0° 45']	-0° 58' [-0° 45' \pm 0° 45']		
キャスター 〔純正値〕 (Caster [Stock Measurements])	+5° 03' [+5° 10' ± 1° 00']	-		
	最低地上高データ (Vehicle Height Data)			
最低地上高場所 〔数値mm〕 (Minimum ground elevation 〔Numerical data mm〕)	フロントサスペンションメンバー左側 〔116mm〕			

■ Precautions During Installation

• The rear service panel is recommended to be modified for easy access to the damping force adjustment dials.