

Additional applications for the DAMPER ZZ-R has been confirmed for the Subaru XV (GT3,GT7)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

[Click here for further information on DAMPER ZZ-R](#)



Front : -34mm Down / Rear : -44mm Down

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
SUBARU							
XV	2017/05-	GT3,GT7	FB16,FB20	¥187,000	¥170,000	92564	4959094925644

Product Description

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification

	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Coilovers
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	5.0	5.0
Free Length of Spring mm	200	220
Spring Type※	ST	ST
Ride Height Adjustability mm	-65 ~ 0	-65 ~ 0



■ Remarks : GTE Unchecked. Ride height adjustability data from GT7.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, variable Specific Springs」

※Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	MSRP w/tax	MSRP	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	¥66,000	¥60,000	Upgrade to the DSC Plus with the vehicle specific set

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
SUBARU	XV	GT7	2019年1月	2.0i-L Eye Sight

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重 (kg) (Vehicle Weight)	1430		
	軸重(kg) (Axle Weight)	860	570	
	タイヤサイズ (Tire Size)	225/55R18	225/55R18	
	ホイールサイズ (Wheel Size)	18inch 7.0J Inset48	18inch 7.0J Inset48	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	-0°02'	-0°02'	
	キャンバー (Camber)	-1°31'	-3°06'	
	キャスター (Caster)	+6°15'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	5.0	5.0	
	スプリング自由長(mm) (Free Length of Spring)	200	220	
	スプリング内径(mm) (Spring Inner Diameter)	Φ62	Φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	
	テスト時減衰力 (Tested Damping force)	16段	16段	
	地面~フェンダー(mm) (Ground~Fender)	731	728	
	基準車高(mm) (Difference from Stock)	-34	-44	
	車高調整範囲(mm) (Height Adjustment Range)	-65~0	-65~0	
	最低地上高(mm) (Minimum Ground Clearance)	150mm (プロペラシャフト下触媒)		

Product Description

- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Lower your vehicle for a stylish look..
- Increase the damping force for high speed stability.
- Decrease the damping force to soften the ride quality on rough terrain.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.