

Additional applications for the DAMPER ZZ-R SpecDSC Plus has been confirmed for the Subaru Levorg (VN5 GT)



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.



Front : -35mm Down / Rear : -27mm Down

[Click here for further information on DAMPER ZZ-R Spec DSC PLUS](#)

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
SUBARU							
LEVORG	2020/10-	VN5	CB18	¥247,500	¥225,000	98580	4959094985808

Product Description

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Information	Product Information	
	Front	Rear
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Coilovers
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.0	6.0
Free Length of Spring mm	180	220
Spring Type	ST	ST
Length Adjustment (mm)	-55 ~ 0	-45 ~ 0



■ Remarks : GT, GT EX, GT-H, GT-H EX Only

※Abbreviation for Spring Types 「ST: ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles

Optional Parts					
Product Name	Code No.	MSRP w/tax	MSRP	Remarks	
DSC PLUS Vehicle Specific Set TYPE-A	15236	¥66,000	¥60,000	Upgrade to the DSC Plus with the vehicle specific set	
DSC PLUS GPS Sensor Kit	15235	¥11,000	¥10,000	Vehicle speed can be easily inputted	
DSC PLUS Remote Switch	15219	¥3,300	¥3,000	Allows you to conveniently switch settings.	

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
SUBARU	LEVORG	VN5	2020年11月	GT-H EX

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重 (kg) (Vehicle Weight)	1570		
	軸重(kg) (Axle Weight)	930	640	
	タイヤサイズ (Tire Size)	225/45R18	225/45R18	
	ホイールサイズ (Wheel Size)	18inch 7.5J Inset55	18inch 7.5J Inset55	
	レバール比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	-0°05'	-0°01'	
	キャンバー (Camber)	-1°01'	-1°34'	
	キャスター (Caster)	+6°02'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	6.0	6.0	
	スプリング自由長(mm) (Free Length of Spring)	180	220	
	スプリング内径(mm) (Spring Inner Diameter)	Φ62	Φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	DSC Plus装着時 32,64,96段へ変更可能
	テスト時減衰力 (Tested Damping force)	16段	16段	
	地面~フェンダー(mm) (Ground~Fender)	654	660	
	基準車高(mm) (Difference from Stock)	-35	-27	
	車高調整範囲(mm) (Height Adjustment Range)	-55~0	-45~0	
	最低地上高(mm) (Minimum Ground Clearance)	117mm (マフラータイコ2個目)		

Product Description

- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Lower your vehicle for a stylish look..
- The pillow ball upper mount allows you to make camber adjustments to the front suspension.
- The product includes a shortened stabilizer link to optimize roll control.
- When driving at speeds of over 80km/h, increasing the damping force by 4 steps will stabilize the ride quality.
- Please check the following website to access the DSC PLUS Setting Data for individual vehicles.