

Additional applications for the DAMPER ZZ-R has been confirmed for the SUZUKI JIMNY SIERRA (JB74W)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further information on DAMPER ZZ-R](#)



Front : +22mm(0.9in) Up / Rear : +20mm(0.8in)

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
SUZUKI							
JIMNY SIERRA	2018/07-	JB74W	K15B	¥161,700	¥147,000	92524	4959094925248

**Product Specification**

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Separate	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Spring Rate kgf/mm	2.3	3.0
Free Length of Spring mm	300	RL:240 / RR:255
Spring Type※	BS	BS
Ride Height Adjustability mm	0 ~ +30	0 ~ +30



■ Remarks : AT/MT compatible. Front and rear damping force adjustment dials are located inside the wheel well.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

# DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
SUZUKI	JIMNY SIERRA	JB74W	2021年8月	JC

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重 (kg) (Vehicle Weight)	1090		
	軸重(kg) (Axle Weight)	610	480	
	タイヤサイズ (Tire Size)	195/80R15	195/80R15	
	ホイールサイズ (Wheel Size)	15inch 5.5J Inset5	15inch 5.5J Inset5	
	レバー比 (Lever Ratio)	1.1	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	+0°00'	+0°04'	
	キャンバー (Camber)	+0°31'	-0°31'	
	キャスター (Caster)	+0°55'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	2.3	3.0	
	スプリング自由長(mm) (Free Length of Spring)	300	RL:240 / RR:255	
	スプリング内径(mm) (Spring Inner Diameter)	φ86.5 - 【φ110】 - φ85	φ86.5 - 【φ110】 - φ83	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	
	テスト時減衰力 (Tested Damping force)	16段	16段	
	地面~フェンダー(mm) (Ground~Fender)	810	825	
	基準車高(mm) (Difference from Stock)	+22	+20	
	車高調整範囲(mm) (Height Adjustment Range)	0~+30	0~+30	
	最低地上高(mm) (Minimum Ground Clearance)	203mm (フロント右側アーム 前側)		

## Product Description

- Lift up suspension.
- Raise the ride height of the vehicle for a more aggressive look.
- The spring rate has been optimized to make sure the vehicle will be stable even during high speeds.
- Sufficient compression and rebound strokes have been set for optimal ride quality.
- Change the damping force according to the number of passengers to optimize ride quality.
- Damper ZZ-R for lowering (Code No. 92525) available as well.