

Additional applications for the DAMPER ZZ-R SpecDSC Plus Lift Up Version has been confirmed for the Mitsubishi DELICA D:5 (CV1W/CV5W) / DELICA D:5 URBAN GEAR (CV1W)



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.



Click here for further information on DAMPER ZZ-R Spec DSC PLUS

Front : +30mm(1.2in) Up / Rear : +30mm(1.2in) Up

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MITSUBISHI							
DELICA D:5	2007/01-	CV5W	4B12				
DELICA D:5	2013/01-	CV1W	4N14	¥303,600	¥276,000	98587	4959094985877
DELICA D:5 URBAN GEAR	2019/02-						

Product Description

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	7.0	8.5			
Free Length of Spring mm	220	300			
Spring Type*	ST	BS			



■ Remarks: Lift Up Version

*Abbreviation for Spring Types \[ST: ID62 Straight Spring \], \[FBS: Barrel or Tapered, Vehicle Specific Springs \]

*Adjustability in ride height may vary between vehicles.

Optional Parts						
Product Name	Code No.	MSRP w/tax	MSRP	Remarks		
DSC PLUS Vehicle Specific Set TYPE-A	15236 ¥66,000		¥60,000	Upgrade to the DSC Plus with the		
				vehicle specific set		
DSC PLUS GPS Sensor Kit	15235	¥11,000	¥10,000	Vehicle speed can be easily inputted		
DSC PLUS Remote Switch	15219	¥3,300	¥3,000	Allows you to conveniently switch settings.		

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
MITSUBISHI	DELICA D:5	CV5W	2016年3月	G-POWÉR
確認車両情報		フロント	リア	備考
1年10年11月刊		(Front)	(Rear)	(Remarks)
	車重(kg)	1		
	(Vehicle Weight)			
	軸重(kg)	970	800	
 車両情報	(Axle Weight) タイヤサイズ			
早间情報 (Vehicle Information)		235/70R16	235/70R16	
(Verlicle Information)	(Tire Size) ホイールサイズ			
	(Wheel Size)	16inch 7.0J Inset42	16inch 7.0J Inset42	
	レバー比			
	(Lever Ratio)	1.0	1.1	
	\—	222-1	222.1	
	(Toe)	+0°07'	-0°01'	
アライメントデータ	キャンバー	0040	. 0012	
(Alignment Data)	(Camber)	-0°40'	+0°12'	
	キャスター	+2°09'		
	(Caster)	+2°09	1	
DAMPER ZZ-R Spec	2.	フロント	リア	備考
-		(Front)	(Rear)	(Remarks)
	スプリングレート(kgf/mm)	7.0	8.5	
	(Spring Rate)			
	スプリング自由長(mm)	220	300	
	(Free Length of Spring) スプリング内径(㎜)			
	` '	Ф62	Ф80 - Ф84	
	(Spring Inner Diameter) 減衰力調整段数			
	(Damping force Adjustment)	1~32段	1~32段	
DAMPER ZZ-R	テスト時減衰力			DSC Plus装着時
仕様(Spec.)	(Tested Damping force)	16段	16段	32,64,96段へ変更可能
III-M(OPEC.)	地面~フェンダー(mm)			52,01,5000 及又与品
	(Ground~Fender)	850	845	
	基準車高(mm)			
	(Difference from Stock)	+30	+30	
	車高調整範囲(mm)	0- +25	0- +60	
	(Height Adjustment Range)	0~+35	0~+60	
	最低地上高(mm)	24∩mm (マフ=	ラータイコ中央)	
	(Minimum Ground Clearance)	24011111 (47)	/ /1JT天/ 	

Product Description

- Damper ZZ-R Lift Up version.
- Raise the height of your vehicle for a powerful look.
- The spring rate has been refined to be comfortable even after lifting the vehicle.
- The damping force has set to maintain vehicle stability and comfort even during high speeds.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Increase the damping force by 4 clicks when driving over 80km/h to increase high speed stability.