

Additional applications for the DAMPER ZZ-R has been confirmed for the LEXUS NX (AAZA2#, AAZH2#, TAZA25)





Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

Click here for further details on DAMPER ZZ-R



(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
LEXUS							
NX	2021/11-	AAZA20,AAZA25, AAZH20,AAZH25, AAZH26,TAZA25	A25A-FKS, A25A, T24A-FTS	¥217,800	¥198,000	92588	4959094925880

Product Description

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	6.0	7.0			
Free Length of Spring mm	220	220			
Spring Type※	ST	BS			
Ride Height Adjustability mm	-85 ∼ -25	-70 \sim -25 (-10)			



■ Remarks: Rear Damping force adjustment dials are located inside the wheel well. 2WD/4WD compatible.

Can be installed on vehicles equipped with AVS but the AVS function cannot be used.

 $\label{lem:spring_princh} \mbox{\mathbb{K} Abbreviation for Spring Types ΓST:ID62 Straight Spring], ΓBS:Barrel or Tapered, V ehicle Specific Springs Γ and Γ is the specific Springs Γ is the springs Γ is the specific Springs Γ is the springs Γ is the springs Γ is the springs Γ is the sprin$

*Adjustability in ride height may vary between vehicles.

Optional Parts						
Product Name	Code No.	MSRP w/tax	MSRP	Remarks		
DSC PLUS Vehicle Specific Set TYPE-A	15236	¥77,000	¥70,000	Upgrade to the DSC Plus with the vehicle specific set		

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
LEXUS	NX350	TAZA25	2021年12月	F SPORT

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	18		
	軸重(kg) (Axle Weight)	1090	730	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	235/50 R20	235/50 R20	
	ホイールサイズ (Wheel Size)	20inch 7.5J Inset35	20inch 7.5J Inset35	
	レバー比 (Lever Ratio)	1.0	1.1	
	├ - (Toe)	+0°04'	+0°00'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-1°29'	-2°08'	
	キャスター (Caster)	+5°14'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	7.0	
	スプリング自由長(mm) (Free Length of Spring)	220	220	
	スプリング内径(mm) (Spring Inner Diameter)	Ф62	Ф62.5-(Ф104)-Ф62.5	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	
DAMPER ZZ-R 仕様(Spec.)	テスト時減衰力 (Tested Damping force)	20段	16段	
	地面〜フェンダー(mm) (Ground〜Fender)	764	770	
	基準車高(mm) (Difference from Stock)	-45	-38	
	車高調整範囲(mm) (Height Adjustment Range)	-85~-25	-70~-25 (-10)	() 内スペーサー使用時
	最低地上高(㎜) (Minimum Ground Clearance)	155mm(マフラー中間タイコ前側)		

Product Description

- Body roll has been limited for improved cornering performance.
- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.