


Additional applications for the DAMPER ZZ-R SpecDSC Plus  
has been confirmed for the HONDA CIVIC TYPE-R (FL5)



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.



Front : 20mm Down / Rear : 26mm Down

[Click here for further information on DAMPER ZZ-R Spec DSC PLUS](#)

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
HONDA					
CIVIC TYPE-R	2022/09-	FL5	K20C	98395	4959094983958

**Product Description**

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification		
	Front	Rear
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Spring Rate kgf/mm	12.0	10.0
Free Length of Spring mm	160	165
Spring Type※	ST	BS
Ride Height Adjustability mm	-50 ~ 0	-40 ~ -10

■ Remarks : Includes Canceled. Installable on vehicles equipped with adjustable damping force. However, you will not be able to adjust the damping force using the vehicle electronics. Rear damping force dial located inside the wheel well.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.



Optional Parts			
Product Name	Code No.	Remarks	
DSC PLUS Vehicle Specific Set TYPE-E	15240	Upgrade to the DSC Plus with the vehicle specific set	
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted	
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.	

# DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
HONDA	CIVIC	FL5	2022年9月	TYPE-R

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重 (kg) (Vehicle Weight)	1430		
	軸重(kg) (Axle Weight)	890	540	
	タイヤサイズ (Tire Size)	265/30 R19	265/30 R19	
	ホイールサイズ (Wheel Size)	19inch 9.5J Inset60	19inch 9.5J Inset60	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	+0°05'	-0°01'	
	キャンバー (Camber)	-2°07'	-2°39'	
	キャスター (Caster)	+7°37'	—	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	12.0	10.0	
	スプリング自由長(mm) (Free Length of Spring)	160	165	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - (φ130) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1～32段	1～32段	
	テスト時減衰力 (Tested Damping force)	16段	16段	DSC Plus装着時 32,64,96段へ変更可能
	地面～フェンダー(mm) (Ground～Fender)	653	645	
	基準車高(mm) (Difference from Stock)	-20	-26	
	車高調整範囲(mm) (Height Adjustment Range)	-50 ～ 0	-40 ～ -10	
	最低地上高(mm) (Minimum Ground Clearance)	122mm (中間タイコ前マフラーパイプ)		

## Product Description

- Body roll has been limited for improved cornering performance.
- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the optimal DSC PLUS, the damping force can be controlled from inside the vehicle.