

Additional applications for the DAMPER ZZ-R SpecDSC Plus have been confirmed for the TOYOTA COROLLA(HYBRID) / COROLLA SPORT(HYBRID) / COROLLA TOURING(HYBRID) (MZEA17 / MZEA12H / ZWE219H / ZWE219W )



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.



Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
ТОУОТА					
COROLLA HYBRID		ZWE219	2ZR-1VM		
COROLLA SPORT		MZEA12H	M20A-FKS		
COROLLA SPORT HYBRID	2022/10-	ZWE219H	2ZR-1VM	98512	4959094985129
COROLLA TOURING		ZWE215W,	2ZR-1VM,		
HYBRID		ZWE219W	2ZR-1VM-1WM		

## **Product Description**

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification					
	Front	Rear			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	4.0	4.0			
Free Length of Spring mm	220	240			
Spring Type※	ST	BS			
		05 0			



Ride Height Adjustability mm -50 ~ 0 -35 ~ 0 \*\*Abbreviation for Spring Types 1ST:ID62 Straight Spring J, FBS:Barrel or Tapered, Vehicle Specific Springs J

\*Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.

## DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
TOYOTA	COROLLA TOURING	ZWE219W	2023年3月	HYBRID W×B

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1390		
	軸重(kg) (Axle Weight)	840	550	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	215/45 R17	215/45 R17	
	ホイールサイズ (Wheel Size)	17inch 7.5J Inset50	17inch 7.5J Inset50	
	レバー比 (Lever Ratio)	1.0	1.1	
	├- (Toe)	+0°05'	+0°11'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-1°32'	-1°44'	
	キャスター (Caster)	+6°53'	-	

DAMPER ZZ-R Spec	c.	フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	4.0	4.0	
	スプリング自由長(mm) (Free Length of Spring)	220	240	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - (φ115) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	DSC Plus装着時 32,64,96段へ変更可能
	テスト時減衰力 (Tested Damping force)	16段	16段	
	地面〜フェンダー(mm) (Ground〜Fender)	641	639	
	基準車高(mm) (Difference from Stock)	-30	-27	
	車高調整範囲(㎜) (Height Adjustment Range)	-50 ∼ 0	-35 ∼ 0	
	最低地上高(mm) (Minimum Ground Clearance)	95mm (フロントメンバー後方ボルト)		

## **Product Description**

- Body roll has been limited for improved cornering performance.
- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.