

Additional applications for the DAMPER ZZ-R SpecDSC Plus has been confirmed for the NISSAN ARIYA (FE0)



Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.





Front : 26mm Down / Rear : 35mm Down

Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
NISSAN					
ARIYA	2021/06-	FE0	AM67	98631	4959094986317

Product Description

• Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes

depending on variables such as road condition and number of passengers.

• The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.

• The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.

• During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.

• Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.

• With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification							
	Front	Rear					
Length Adjustment	0	0					
Shock Absorber Structure	Coilovers	Separate					
Upright or Inverted	Upright	Upright					
Upper Mount	Reinforced Rubber	Reinforced Rubber					
Spring Rate kgf/mm	6.0	8.0					
Free Length of Spring mm	220	250					
Spring Type※	ST	BS					
Ride Height Adjustability mm	-60 \sim 0	-45 \sim -20					



Remarks : Unchecked with 4WD, B9.

** Abbreviation for Spring Types [ST:ID62 Straight Spring], [BS:Barrel or Tapered, Vehicle Specific Springs] ** Adjustability in ride height may vary between vehicles.

Optional Parts

	Product Name	Code No.	Remarks			
	DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set			
	DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted			
D	DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.			



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

	型式	年 式	グレード
			(Grade)
			B6 Limited
, , , , , , , ,			Do Linited
	フロント	リア	備考
			(Remarks)
車重 (kg)	1960		,,,
軸重(kg)	1050	010	
(Axle Weight)	1050	910	
	235/55 P10	235/55 P10	
	255/55 119	255/55 119	
	19inch 7 51 Inset40	19inch 7.51 Inset40	
		15mcm 7.55 mset+0	
	1.0	1.3	
	+0°05'	+0°01'	
		-2°26'	
	-0°55'		
	+6°08'	-	
			<u> </u>
DAMPER ZZ-R Spec.		リア	備考
		(Rear)	(Remarks)
スプリングレート(kgf/mm)	6.0	8.0	
(Spring Rate)			
	220	250	
	220	250	
	ω62	φ78.5 -(φ130)- φ72.5	
	ψ 0 2		
	1~32段	1~32段	DSC Plus装着時
			32,64,96段へ変更可能
	16段	16段	
	757	745	
	-26	-35	
	-60 \sim 0	-45 \sim -20	
		ッキアップポイント)	
最低地上高(mm)	100 (117)		
	(Vehicle Weight) 軸重(kg) (Axle Weight) タイヤサイズ (Tire Size) ホイールサイズ (Wheel Size) レバー比 (Lever Ratio) トー (Toe) キャンバー (Camber) キャスター (Caster) スプリングレート(kgf/mm) (Spring Rate) スプリング内督由長(mm) (Free Length of Spring) スプリング内径(mm) (Spring Inner Diameter) 減衰力調整段数 (Damping force Adjustment) テスト時減衰力 (Tested Damping force) 地面 ~7ェンダー(mm) (Ground~Fender) 基準車高(mm) (Difference from Stock) 車高調整範囲(mm) (Height Adjustment Range)	(Vehicle Name)(Model)ARIYAFE0第単(kg) $7\Box > h$ (Front)車重(kg)1050輸量(kg)1050(Axle Weight)1050タイヤサイズ235/55 R19(Tire Size)19inch 7.5J Inset40(Wheel Size)19inch 7.5J Inset40レバー比1.0レビー比1.0トー+0°05'(Toe)+0°05'ギャンパー-0°55'(Camber)-0°55'(Caster)ブロント (Front)スプリングレート(kgf/mm) (Spring Rate)6.0スプリングレート(kgf/mm) (Spring Inner Diameter)220ズブリング内福(mm) (Spring force Adjustment) $\eta62$ 減衰力調整段数 (Tested Damping force)16段地面 ~7x/ダ-(mm) (Ground~Fender)757基準車高(mm) (Difference from Stock)-26車高調整範囲(mm) (Height Adjustment Range)-60 ~ 0	(Vehicle Name) (Model) (Model Year) ARIYA FE0 2022年3月 フロント リア (Front) リア (Rear) 車重 (kg) 1960 (Vehicle Weight) 1050 910 人本ke Weight) 1050 910 タイヤサイズ 235/55 R19 235/55 R19 (Keer) 19inch 7.5J Inset40 19inch 7.5J Inset40 (Wheel Size) 19inch 7.5J Inset40 19inch 7.5J Inset40 (Lever Ratio) 1.0 1.3 トー +0°05' +0°01' (Toe) +0°05' -2°26' キャスター +6°08' - (Caster) 7ロント IJア (Front) (Rear) - スプリングレート(kg/nm) 6.0 8.0 スプリング内由観長(mm) 220 250 (Free Length of Spring) 220 250 (Free Length of Spring) 1~328p 1~328p アノリング内晶長(mm) 662 $\phi78.5 - (\phi130) - \phi72.5$ (Spring Inner Diameter) 328p 1~328p

Product Description

Body roll has been limited for improved cornering performance.

- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.