

## Additional applications for the DAMPER ZZ-R have been confirmed for the TOYOTA VOXY/ESQUIRE/NOAH (ZRR85G/ZRR85W)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

Click here for further details on DAMPER ZZ-R





(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)	
TOYOTA	TOYOTA					
VOXY	2014/01-2022/01	70000				
ESQUIRE	2014/10-	ZRR85G, ZRR85W	3ZR-FAE	92637	4959094926375	
NOAH	2014/01-2022/01					

## **Product Description**

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Stock			
Spring Rate kgf/mm	6.0	7.0			
Free Length of Spring mm	240	220			
Spring Type※	ST	BS			
Ride Height Adjustability mm	-35 ∼ 0	-55 ∼ <b>-</b> 0			



■ Remarks: 4WD Only. Unchecked with Well cab. Information on ride height from ZRR85G (NOAH).

\*\*Abbreviation for Spring Types \[ ST: \] ID62 Straight Spring \], \[ \] FS: Barrel or Tapered, \[ Vehicle Specific Springs \] \[ \] Adjustability in ride height may vary between vehicles.

Optional Parts					
Product Name	Code No.	Remarks			
DSC PLUS Vehicle Specific Set TYPE-G	15242	Upgrade to the DSC Plus with the			
		vehicle specific set			

## DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
TOYOTA	NOAH	ZRR85G	2021年12月	X

7-6-27 -+- 77-4-4-10		フロント	リア	備考
確認車両情報		(Front)	(Rear)	(Remarks)
	車重(kg) (Vehicle Weight)	1650		
	軸重(kg) (Axle Weight)	930	720	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	195/65 R15	195/65 R15	
	ホイールサイズ (Wheel Size)	15inch 6.0J Inset50	15inch 6.0J Inset50	
	レバー比 (Lever Ratio)	1.0	1.1	
	├─ (Toe)	+0°05'	+0°13'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-2°02'	-1°11'	
	キャスター (Caster)	+3°35'	_	

DAMPER ZZ-R Spec	c.	フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	6.0	7.0	, , ,
	スプリング自由長(mm) (Free Length of Spring)	240	220	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - (φ109) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	685	711	
	基準車高(mm) (Difference from Stock)	-10	-43	
	車高調整範囲(mm) (Height Adjustment Range)	-35 ∼ 0	-55 ∼ 0	
	最低地上高(㎜) (Minimum Ground Clearance)	118mm (マフラ-	-タイコ3個目前側)	

初めてご使用される際の推奨減衰力	20€Љ	⊃CFЉ	左記に記載の減衰に合わせ
(Recommended Damping force)	20段	26段	てからご使用ください

## **Product Description**

- Body roll has been limited for improved cornering performance.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Rear suspension optimized for comfortable ride quality for 2<sup>nd</sup> and 3<sup>rd</sup> row seats.
- The ride height has been adjusted to make the vehicle silhouette look flatter.
- As a 4WD vehicle there are plenty of ride height adjustability for lowering as well as increasing the height from the default setting.
- Increase the damping force by 4~6 clicks when traveling at speed higher than 80km for a more stable ride.