

## Additional applications for the DAMPER ZZ-R have been confirmed ABARTH ABARTH595 (312142)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

Click here for further details on DAMPER ZZ-R



Front: 11mm Down / Rear: 29mm Down

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)		
ABARTH							
ABARTH595	2013/01-	312142	312A3,312A1	92604	4959094926047		

## **Product Description**

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification						
	Front	Rear				
Damping Force Adjustability	32 Levels	32 Levels				
Length Adjustment	0	0				
Shock Absorber Structure	Coilovers	Separate				
Upright or Inverted	Upright	Upright				
Upper Mount	Stock	Reinforced Rubber				
Spring Rate kgf/mm	5.0	5.0				
Free Length of Spring mm	180	180				
Spring Type※	ST	BS				
Ride Height Adjustability mm	-60 ∼ 0	-40 ∼ -5				



Remarks: Rear damping force adjustment dials are located inside the wheel well.
AT/MT Compatible. Compatibly only tested with vehicles sold in Japan. Compatible with all grades.

Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS:Barrel or Tapered, Vehicle Specific Springs」

%Adjustability in ride height may vary between vehicles.

## DAMPER ZZ-R Spec & Vehicle Information

車名



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

型式

<i>&gt; 13</i>	<del>+</del> 1	土厶	+10	7V 1
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
ABARTH	ABARTH595	312142	2016年12月	COMPETIZIONE
確認車両情報		フロント	リア	備考
		(Front)	(Rear)	(Remarks)
	車重(kg)	1120		
	(Vehicle Weight)	1	120	
	軸重(kg)	730	390	
	(Axle Weight)	730		
車両情報	タイヤサイズ	205/40 R17	205/40 R17	
(Vehicle Information)	(Tire Size)	203/40 1(17		
	ホイールサイズ	17inch 7.0J Inset38	17inch 7.0J Inset38	
	(Wheel Size)	17111011 7.03 11130030		
	レバー比	1.0	1.1	
	(Lever Ratio)	1.0		
	<b>&gt;</b> -	-0°03'	+0°32'	
アライメントデータ	(Toe)	0 03	+0 32	
	キャンバー	-1°08'	-1°04'	
(Alignment Data)	(Camber)	1 00	101	
	キャスター	+3°17'	_	
	(Caster)			
DAMPER ZZ-R Spec.		フロント	リア	備考
		(Front)	(Rear)	(Remarks)
	スプリングレート(kgf/mm)	5.0	5.0	
	(Spring Rate)			
	スプリング自由長(mm)	180	180	
	(Free Length of Spring)			
DAMPER ZZ-R 仕様(Spec.)	スプリング内径(mm)	φ62	φ104 - (φ130) - φ96.5	
	(Spring Inner Diameter)			
	減衰力調整段数	1~32段	1~32段	
	(Damping force Adjustment) 地面〜フェンダー(mm)		608	
	・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	603		
	(Ground~Fender) 基準車高(mm)			
	参学早向(IIIII) (Difference from Stock)	-11	-29	
	(Dillerence Holli Stock)	1	1	

初めてご使用される際の推奨減衰力	4.CED.	4.650.	左記に記載の減衰に合わせ
(Recommended Damping force)	16段	16段	てからご使用ください

 $-60 \sim 0$ 

 $-45 \sim -10$ 

99mm (触媒)

## **Product Description**

メーカー

■ Vehicle specific rear bump rubber and cover for the front upper mount are included.

車高調整範囲(mm)

(Height Adjustment Range) 最低地上高(mm)

(Minimum Ground Clearance)

- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Lower your vehicle for a stylish look.
- Camber can be adjusted from the front lower bracket.