

Additional applications for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the TOYOTA GR COROLLA (GZEA14H)



Front: 26mm Down / Rear: 29mm Down

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
ΤΟΥΟΤΑ			-		
GR COROLLA	2022/12-	GZEA14H	G16E-GTS	98620	4959094986201

Product Description

 Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.

The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.

• The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.

 During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.

• Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.

• With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification					
	Front	Rear			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Reinforced Rubber			
Spring Rate kgf/mm	6.0	7.0			
Free Length of Spring mm	200	220			
Spring Type※	ST	BS			
Ride Height Adjustability mm	-45 \sim 0	-60 \sim -15			



Remarks : Unchecked with RZ Morizo Editoin. Rear damping force adjustment located inside the wheel well. *Abbreviation for Spring Types [ST:ID62 Straight Spring], [BS:Barrel or Tapered, Vehicle Specific Springs] %Adjustability in ride height may vary between vehicles.

Optional Parts				
Product Name	Code No.	Remarks		
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set		
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted		
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.		



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
ΤΟΥΟΤΑ	GR COROLLA	GZEA14H	2023年4月	RZ

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1470		
	軸重(kg) (Axle Weight)	880	590	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	235/40 R18	235/40 R18	
	ホイールサイズ (Wheel Size)	18inch 8.5J Inset30	18inch 8.5J Inset30	
	レバー比 (Lever Ratio)	1.0	1.1	
	トー (Toe)	-0°06'	-0°09'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-2°25'	-2°56'	
	キャスター (Caster)	+6°39'	_	

DAMPER ZZ-R Spec		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	7.0	
	スプリング自由長(mm) (Free Length of Spring)	200	220	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - (φ104) - φ62	
DAMPER ZZ-R 仕様(Spec.)	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	649	656	
	基準車高(mm) (Difference from Stock)	-26	-29	
	車高調整範囲(mm) (Height Adjustment Range)	$-45 \sim 0$	-60 \sim -15	
	最低地上高(mm) (Minimum Ground Clearance)	93mm (アンダーパネル固定ボルト)		
	用される際の推奨減衰力	16段	10段	左記に記載の減衰に合わせ

Product Description

- Vehicle stability has been maintained while improving the handling to be sporty.
- Body roll has been limited for improved cornering performance.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Increase the damping force to improve vehicle stability at higher speeds.
- Decrease the damping force for a smoother ride quality.

(Recommended Damping force)

- Optional Front Upper Mount can be installed. For product compatibility please check our website.
- Increase the damping force by 4~6 click for speeds above 80km/h to improve vehicle stability.

てからご使用ください