

Additional applications for the DAMPER ZZ-R has been confirmed for LEXUS RZ/SUBARU SOLTERRA (XEAM15/YEAM15X)



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

[Click here for further details on DAMPER ZZ-R](#)



Front : 33mm Down / Rear : 39mm Down

(Vehicle)	(Model Year)	(Model)	(Motor Model)	(Code No.)	(JAN Code)
LEXUS					
RZ	2023/03-	XEBM15	1XM-1YM	92622	4959094926221
SUBARU					
SOLTERRA	2022/05-	YEAM15X	1YM-1YM	92622	4959094926221

Product Description

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Reinforced Rubber	Reinforced Rubber
Spring Rate kgf/mm	6.5	8.2
Free Length of Spring mm	220	260
Spring Type※	BS	BS
Ride Height Adjustability mm	-70 ~ 0	-55 ~ -15



■ Remarks : Unchecked with XEAM10. Rear damping force adjustment located inside the wheel well. ※DSC Plus recommended
Data on Vehicle ride height from XEBM15.

※Abbreviation for Spring Types 「ST:ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

Optional Parts		
Product Name	Code No.	Remarks
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
LEXUS	RZ	XEBM15	2023年6月	First Edition

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重(kg) (Vehicle Weight)	2110		
	軸重(kg) (Axle Weight)	1130	980	
	タイヤサイズ (Tire Size)	235/50 R20	255/45 R20	
	ホイールサイズ (Wheel Size)	20inch 8.0J Inset35	20inch 9.5J Inset35	
	レバー比 (Lever Ratio)	1.0	1.1	
アライメントデータ (Alignment Data)	トー (Toe)	+0°09'	+0°10'	
	キャンバー (Camber)	-1°38'	-1°52'	
	キャスター (Caster)	+5°33'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	6.5	8.2	
	スプリング自由長(mm) (Free Length of Spring)	220	260	
	スプリング内径(mm) (Spring Inner Diameter)	φ62 - (φ109) - φ62	φ62 - (φ115) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	DSC Plus装着時 32,64,96段へ変更可能
	地面~フェンダー(mm) (Ground~Fender)	765	762	
	基準車高(mm) (Difference from Stock)	-33	-39	
	車高調整範囲(mm) (Height Adjustment Range)	-70 ~ 0	-55 ~ -15	
	最低地上高(mm) (Minimum Ground Clearance)	171mm (フロントメンバー中央)		
初めてご使用される際の推奨減衰力 (Recommended Damping force)		24段	24段	左記に記載の減衰に合わせて からご使用ください

Product Description

- Vehicle stability has been maintained while improving the handling to be sporty.
- Body roll has been limited for improved cornering performance.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- Increase the damping force to improve vehicle stability at higher speeds.
- Decrease the damping force for a smoother ride quality.
- Can be installed with the optional DAMPER ZZ-R Spec.DSC PLUS.
- By installing the Optional DSC PLUS vehicle specific kit, the damping force can be easily adjusted from inside the vehicle.