

## Additional applications for the DAMPER ZZ-R Spec DSC Plus has been confirmed for the TOYOTA GR COROLLA (GZEA14H)

# DAMPER ZZ-R DSC+

Coil-over suspensions kit with electronically adjustable damping force. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.







Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
TOYOTA					
GR COROLLA	2025/03-	GZEA14H	G16E-GTS	98620	4959094986201

#### **Product Description**

- Click here for price and availability
- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification				
	Front	Rear		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Reinforced Rubber	Reinforced Rubber		
Spring Rate kgf/mm	6.0	7.0		
Free Length of Spring mm	200	220		
Spring Type※	ST	BS		
Ride Height Adjustability mm	-45 ∼ 0	-60 $\sim$ -15		



- Remarks: Compatilbe with AT/MT. Data on ride height from MT.
- \*\*Abbreviation for Spring Types \(^{\text{ST}}:\) ID62 Straight Spring \(^{\text{FBS}}:\) Barrel or Tapered, Vehicle Specific Springs \(^{\text{SP}}:\)

※Adjustability in ride height may vary between vehicles.

Optional Parts					
Product Name	Code No.	Remarks			
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the			
DOCT LOG Verlicle Opecific Set TTT L-A	10200	vehicle specific set			
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted			
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.			
GZEA14H FRONT PILLOW UPPER	00000 EUDDD	Metal panel above upper mount must be modified or			
MOUNT 1SET	92620-FUPRP	removed to make adjustments to the camber angle.			

### DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
TOYOTA	GR COROLLA	GZEA14H	2025年3月	RZ

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1490		
車両情報 (Vehicle Information)	軸重(kg) (Axle Weight)	890	600	
	タイヤサイズ (Tire Size)	235/40 R18	235/40 R18	
	ホイールサイズ (Wheel Size)	18inch 8.5J Inset30	18inch 8.5J Inset30	
	レバー比 (Lever Ratio)	1.0	1.1	
	├─ (Toe)	+0°01'	+0°03'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-2°17'	-2°48'	
	キャスター (Caster)	+6°28'	_	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	7.0	
	スプリング自由長(mm) (Free Length of Spring)	200	220	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ62 - (φ104) - φ62	
DAMPER ZZ-R	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
仕様(Spec.)	地面〜フェンダー(mm) (Ground〜Fender)	650	654	
	基準車高(mm) (Difference from Stock)	-25	-23	
	車高調整範囲(mm) (Height Adjustment Range)	-45 ∼ 0	-60 ∼ -15	
	最低地上高(mm) (Minimum Ground Clearance)	96mm (アンダー	パネル固定ボルト)	

初めてご使用される際の推奨減衰力	22 <b>€</b> ₽	26€₽	左記に記載の減衰に合わせ
(Recommended Damping force)	22段	26段	てからご使用ください

### **Product Description**

- Compatibility for vehicles after the minor change.
- Vehicle stability has been maintained while improving the handling to be sporty.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the DSC Plus kit, the wiper cowl does not need to be modified and allow the damping force to be controlled from inside the vehicle. ※ Modification will need to be made when installing the optional pillow upper mount,
- Optional Front Upper Mount can be installed. For product compatibility please check our website.
- Increase the damping force by 4~6 click for speeds above 80km/h to improve vehicle stability.